

COO-VAR®

PAINTS, PRIMERS AND SPECIALISED COATINGS

SAFETY DATA SHEET

130/M200 - C.S.P. MORTAR - BASE RESINS

According to Regulation (EC) No 1907/2006, Annex II, as amended. Commission Regulation (EU) No 2015/830 of 28 May 2015.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name 130/M200 - C.S.P. MORTAR - BASE RESINS
Product number 130/M200/1 - BASE

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses BASE FOR TWO COMPONENT Crack and hole filler For professional users only.
Uses advised against NOT SUITABLE FOR FOR USE IN HOMEWORKER (DIY) APPLICATIONS

1.3. Details of the supplier of the safety data sheet

Supplier COO-VAR
 Lockwood Street
 Hull
 HU2 0HN
 +44 (0) 1482 328053(T)
 +44 (0) 1482 219266(F)
 info@coo-var.co.uk

Contact person Technical Department -, 08.30 - 16.30 hrs Mon - Thurs, 08.30 - 15.00 hrs Fri, as above

1.4. Emergency telephone number

Emergency telephone +44 (0) 1482 328053 (08.30 - 16.30 hrs Mon - Thurs, 08.30 - 15.00 hrs Fri)
SDS No. 10792

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Flam. Liq. 2 - H225

Health hazards Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Skin Sens. 1 - H317 Carc. 1B - H350 STOT SE 3 - H335

Environmental hazards Aquatic Chronic 3 - H412

Classification (67/548/EEC or 1999/45/EC) Xn;R20/21/22. Xi;R37/38. R43. F;R11. R33.

2.2. Label elements

Pictogram



130/M200 - C.S.P. MORTAR - BASE RESINS

Signal word	Danger
Hazard statements	H225 Highly flammable liquid and vapour. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H332 Harmful if inhaled. H335 May cause respiratory irritation. H350 May cause cancer. H412 Harmful to aquatic life with long lasting effects.
Precautionary statements	P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261 Avoid breathing vapour/ spray. P264 Wash contaminated skin thoroughly after handling. P271 Use only outdoors or in a well-ventilated area. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P302+P352 IF ON SKIN: Wash with plenty of water. P403+P233 Store in a well-ventilated place. Keep container tightly closed. P501 Dispose of contents/ container in accordance with national regulations.
Contains	METHYL METHACRYLATE, 2-ETHYLHEXYL ACRYLATE, triethyleneglycol dimethacrylate, N,N-DIMETHYL-PARA-TOLUIDINE
Supplementary precautionary statements	P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P308+P313 IF exposed or concerned: Get medical advice/ attention. P312 Call a POISON CENTRE/doctor if you feel unwell. P321 Specific treatment (see medical advice on this label). P332+P313 If skin irritation occurs: Get medical advice/ attention. P333+P313 If skin irritation or rash occurs: Get medical advice/ attention. P362+P364 Take off contaminated clothing and wash it before reuse. P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish. P403+P235 Store in a well-ventilated place. Keep cool. P405 Store locked up.

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

2-ETHYLHEXYL ACRYLATE	30-60%
CAS number: 103-11-7	EC number: 203-080-7
Classification	Classification (67/548/EEC or 1999/45/EC)
Skin Irrit. 2 - H315	R43 Xi;R37/38
Skin Sens. 1 - H317	
STOT SE 3 - H335	
Aquatic Chronic 3 - H412	

130/M200 - C.S.P. MORTAR - BASE RESINS

METHYL METHACRYLATE		30-60%
CAS number: 80-62-6	EC number: 201-297-1	REACH registration number: 01-2119452498-28
Classification Flam. Liq. 2 - H225 Skin Irrit. 2 - H315 Skin Sens. 1 - H317 STOT SE 3 - H335	Classification (67/548/EEC or 1999/45/EC) F;R11 R43 Xi;R37/38	
triethyleneglycol dimethacrylate		1-5%
CAS number: 109-16-0	EC number: 203-652-6	REACH registration number: 01-2119969287-21-0000
Classification Skin Sens. 1B - H317		
N,N-DIMETHYL-PARA-TOLUIDINE		1-5%
CAS number: 99-97-8	EC number: 202-805-4	
Classification Acute Tox. 3 - H301 Acute Tox. 3 - H311 Acute Tox. 2 - H330 Carc. 1B - H350 STOT RE 2 - H373 Aquatic Chronic 3 - H412	Classification (67/548/EEC or 1999/45/EC) T;R23/24/25 R33 R52/53	
N,N-bis-(2-hydroxypropyl)-p-toluidine		<1%
CAS number: 38668-48-3	EC number: 254-075-1	REACH registration number: 01-2119980937-17-0000
Classification Acute Tox. 2 - H300 Eye Irrit. 2 - H319 Aquatic Chronic 3 - H412	Classification (67/548/EEC or 1999/45/EC) T;R25. Xi;R41. R52/53.	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	Remove soiled, soaked clothing immediately. Medical treatment is necessary if symptoms occur which are obviously caused by skin or eye contact with the product or by inhalation of its vapours.
Inhalation	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Consult a physician for specific advice.
Ingestion	Give a few small glasses of water or milk to drink. Never give anything by mouth to an unconscious person. Do not induce vomiting. Get medical attention immediately.

130/M200 - C.S.P. MORTAR - BASE RESINS

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. Get medical attention if irritation persists after washing.

Eye contact Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

4.2. Most important symptoms and effects, both acute and delayed

General information The severity of the symptoms described will vary dependent on the concentration and the length of exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor No specific recommendations. If in doubt, get medical attention promptly.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Do not use water, if avoidable.

5.2. Special hazards arising from the substance or mixture

5.3. Advice for firefighters

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Ensure suitable respiratory protection is worn during removal of spillages in confined areas.

6.2. Environmental precautions

Environmental precautions Avoid the spillage or runoff entering drains, sewers or watercourses. Contain spillage with sand, earth or other suitable non-combustible material. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Provide adequate ventilation. No smoking, sparks, flames or other sources of ignition near spillage. Contain and absorb spillage with sand, earth or other non-combustible material. Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Collect and place in suitable waste disposal containers and seal securely. For waste disposal, see Section 13.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Avoid spilling. Avoid contact with skin and eyes. Keep away from heat, sparks and open flame. Mechanical ventilation or local exhaust ventilation may be required. Observe any occupational exposure limits for the product or ingredients. Avoid inhalation of vapours and spray/mists. The Manual Handling Operations Regulations may apply to the handling of containers of this product. For products sold by weight refer to the guide net weight indicated on the container. Allowance will have to be made for the immediate packaging to give an approximate gross weight.

130/M200 - C.S.P. MORTAR - BASE RESINS

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Keep container tightly closed. Store in closed original container at temperatures between 5°C and 25°C. Isolate from other materials. Protect from light.

Storage class Flammable liquid storage. The storage and use of this product is subject to the Dangerous Substances and Explosive Atmospheres Regulations (DSEAR). The requirements are given in the HSE Approved Code of Practice and Guidance, Storage of Dangerous Substances: DSEAR. Up to 50 litres of liquids with a flashpoint below 32C may be kept in a workroom provided they are kept in closed containers in a marked, fire-resisting cupboard or bin. Larger quantities must be kept in a separate, marked storeroom conforming to the structural requirements contained in the HSE guidance note Storage of Flammable Liquids in Containers.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

METHYL METHACRYLATE

Long-term exposure limit (8-hour TWA): WEL 50 ppm 208 mg/m³

Short-term exposure limit (15-minute): WEL 100 ppm 416 mg/m³

WEL = Workplace Exposure Limit

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate ventilation. Avoid inhalation of vapours. Observe any occupational exposure limits for the product or ingredients.

Personal protection

Keep working clothes separate

Eye/face protection

Wear tight-fitting, chemical splash goggles or face shield.

Hand protection

To protect hands from chemicals, gloves should comply with European Standards EN388 and 374. As a general principle, exposure should be managed by means other than the provision of protective gloves. Manufacturer's performance data suggest that the optimum glove for use should be: Butyl rubber. Thickness: ≥ 0.3 mm Permeation breakthrough time according to EN374 - class: (1-6) e.g. minimum 480 mins. Caution: The performance of gloves under actual working conditions can be significantly affected by many factors and the information provided according to EN374 may not accord with what is achieved in practice. We recommend that expert professional advice is sought that takes into account of the work processes and working environment applicable for each task where gloves are to be worn.

Other skin and body protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact. Wear chemical protective suit.

Hygiene measures

Use engineering controls to reduce air contamination to permissible exposure level. No specific hygiene procedures recommended but good personal hygiene practices should always be observed when working with chemical products. Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly if skin becomes contaminated. Promptly remove any clothing that becomes contaminated.

130/M200 - C.S.P. MORTAR - BASE RESINS

Respiratory protection In confined or poorly-ventilated spaces, a supplied-air respirator must be worn. In case of inadequate ventilation or risk of inhalation of vapours, use suitable respiratory equipment with combination filter (type A2/P3).

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	White Creamy liquid.
Odour	Characteristic. Methacrylate
Flash point	10°C Closed cup.
Relative density	1.02 @ @ 20 C°C
Viscosity	10 - 12 P @ 25 C°C

9.2. Other information

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability Danger of bursting of closed systems due to exothermic polymerisation. Avoid uncontrolled polymerisation. Product polymerises on contact with radical generating substances such as peroxides, azo compounds, heavy metal compounds and solutions. Polymerises easily with evolution of heat. Avoid the following conditions: Avoid contact with peroxides. Heating above 150C causes formation of Hydrogen Chloride.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions May polymerise.

10.4. Conditions to avoid

10.5. Incompatible materials

10.6. Hazardous decomposition products

Hazardous decomposition products Does not decompose when used and stored as recommended.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological effects Acute Dermal Toxicity: LD50 rabbit >5000 mg/kg (methyl methacrylate): >5000 mg/kg (2-ethylhexyl methacrylate). Sensitisation: In sensitisation tests on guinea pigs with and without adjuvant, both positive and negative results were found. In humans various types of allergic reactions have been observed (symptoms: headache, eye irritations, skin affections), related to methy methacrylate. May Cause sensitisation by skin contact - related to 2-ethylhexyl acrylate.

Acute toxicity - oral

ATE oral (mg/kg) 2,217.22

Acute toxicity - dermal

ATE dermal (mg/kg) 11,757.37

Acute toxicity - inhalation

ATE inhalation (gases ppm) 3,919.12

130/M200 - C.S.P. MORTAR - BASE RESINS

ATE inhalation (vapours mg/l)	19.6
ATE inhalation (dusts/mists mg/l)	1.96
Skin contact	Irritating to skin.
Eye contact	Irritating to eyes.
Route of exposure	Inhalation Skin absorption. Ingestion. Skin and/or eye contact.

Toxicological information

1414

SECTION 12: Ecological Information

Ecotoxicity There are no data on the ecotoxicity of this product.

12.1. Toxicity

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hours: 23 - ethylhexyl acrylate mg/l, Fish

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: 17.45 - 2-ethylhexyl acrylate mg/l, Daphnia magna

Acute toxicity - aquatic plants IC₅₀, 72 hours: 44 - ethylhexyl acrylate mg/l, Algae

12.2. Persistence and degradability

12.3. Bioaccumulative potential

12.4. Mobility in soil

Mobility The product hardens to a solid immobile substance.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects Not determined.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information When handling waste, the safety precautions applying to handling of the product should be considered. Waste is classified as hazardous waste. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

130/M200 - C.S.P. MORTAR - BASE RESINS

Waste class

When this coating, in its liquid state, as supplied, becomes a waste, it is categorised as hazardous waste, with code 08 01 11* (SOLVENT BASED LIQUID WASTE). Part-used containers, not drained and/or rigorously scraped out and containing dried residues of the supplied coating, are categorised as hazardous waste, with code 08 01 11* (SOLVENT BASED LIQUID WASTE). Neutralised empty packages, are categorised as non-hazardous waste, with code 15 01 02(plastic packaging) or 15 01 04 (metal packaging) Wear protective clothing during disposal operations. If disposal is by waste contractor, make sure that he has sufficient information and that waste containers are properly labelled. Ideally this component should be mixed with the appropriate hardener and allowed to react fully to produce a solid waste.

SECTION 14: Transport information

General This product is packed in accordance with the Limited Quantity Provisions of CDGCPL2, ADR and IMDG.

14.1. UN number

UN No. (ADR/RID) 1263

UN No. (IMDG) 1866

14.2. UN proper shipping name

Proper shipping name (ADR/RID) Resin solution - containing methyl methacrylate

Proper shipping name (IMDG) Resin solution - containing methyl methacrylate

Proper shipping name (ICAO) Resin solution - containing methyl methacrylate

Proper shipping name (ADN) Resin solution - containing methyl methacrylate

14.3. Transport hazard class(es)

ADR/RID class 3

IMDG class 3

Transport labels



14.4. Packing group

ADR/RID packing group II

IMDG packing group II

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

EmS F-E, S-E

Tunnel restriction code (D/E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

130/M200 - C.S.P. MORTAR - BASE RESINS

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations	The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716).
EU legislation	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended). Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).
Guidance	Workplace Exposure Limits EH40. CHIP for everyone HSG228. Safety Data Sheets for Substances and Preparations. Approved Classification and Labelling Guide (Sixth edition) L131. Dangerous Substances and Explosive Atmospheres Regulations 2002 [L138]

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

General information	Only trained personnel should use this material.
Revision comments	Issued in new format for Reach compliance in accordance with EC 1272/2008 Issued in accordance with Annex II to REACH, as amended by Commission Regulation (EU) No. 2015/830 Correction to classification
Issued by	Technical Dept. (P.E.)
Revision date	18/12/2017
Revision	5
Supersedes date	28/11/2016
SDS number	10792
SDS status	Approved.

130/M200 - C.S.P. MORTAR - BASE RESINS

Risk phrases in full

R10 Flammable.
R11 Highly flammable
R20/21/22 Harmful by inhalation, in contact with skin and if swallowed.
R23/24/25 Toxic by inhalation, in contact with skin and if swallowed.
R25 Toxic if swallowed.
R33 Danger of cumulative effects.
R37/38 Irritating to respiratory system and skin.
R41 Risk of serious damage to eyes.
R43 May cause sensitisation by skin contact.
R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R63 Possible risk of harm to the unborn child.
R66 Repeated exposure may cause skin dryness or cracking.
R67 Vapours may cause drowsiness and dizziness.

Hazard statements in full

H225 Highly flammable liquid and vapour.
H300 Fatal if swallowed.
H301 Toxic if swallowed.
H311 Toxic in contact with skin.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H330 Fatal if inhaled.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H350 May cause cancer.
H373 May cause damage to organs through prolonged or repeated exposure.
H412 Harmful to aquatic life with long lasting effects.

Signature

Initials _____

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.