



## SAFETY DATA SHEET

### 145/W449 - TENNIS COURT PAINT & DRIVE PAINT - ALL COLOURS

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

##### 1.1. Product identifier

**Product name** 145/W449 - TENNIS COURT PAINT & DRIVE PAINT - ALL COLOURS

**Product number** 145/W449/ -

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** Paint.

##### 1.3. Details of the supplier of the safety data sheet

###### Supplier

COO-VAR  
Lockwood Street  
Hull  
HU2 0HN  
+44 (0) 1482 328053(T)  
+44 (0) 1482 219266(F)  
info@coo-var.co.uk

**Contact person** Technical Department -, 08.30 - 16.30 hrs Mon - Thurs, 08.30 - 15.00 hrs Fri, as above

##### 1.4. Emergency telephone number

**Emergency telephone** +44 (0) 1482 328053 (08.30 - 16.30 hrs Mon - Thurs, 08.30 - 15.00 hrs Fri)

#### SECTION 2: Hazards identification

##### 2.1. Classification of the substance or mixture

###### Classification (EC 1272/2008)

**Physical hazards** Not Classified

**Health hazards** Not Classified

**Environmental hazards** Not Classified

##### 2.2. Label elements

##### 2.3. Other hazards

#### SECTION 3: Composition/information on ingredients

##### 3.2. Mixtures

<b>Calcium Carbonate</b>	<b>10-30%</b>
CAS number: 1317-65-3	EC number: 215-279-6

<b>Classification</b>	<b>Classification (67/548/EEC or 1999/45/EC)</b>
Not Classified	-

## 145/W449 - TENNIS COURT PAINT & DRIVE PAINT - ALL COLOURS

<b>Diatomaceous Earth</b>	<b>1-5%</b>
CAS number: 61790-53-2	EC number: 310-127-6
<b>Classification</b> Not Classified	<b>Classification (67/548/EEC or 1999/45/EC)</b> -
<b>Monopropylene glycol</b>	<b>1-5%</b>
CAS number: 57-55-6	EC number: 200-338-0
	REACH registration number: 01-2119456809-23-xxxx
<b>Classification</b> Not Classified	<b>Classification (67/548/EEC or 1999/45/EC)</b> -
<b>Calcium Magnesium Carbonate</b>	<b>1-5%</b>
CAS number: 16389-88-1	EC number: 240-440-2
<b>Classification</b> Not Classified	<b>Classification (67/548/EEC or 1999/45/EC)</b> -

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

<b>General information</b>	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Never give anything by mouth to an unconscious person.
<b>Inhalation</b>	Remove affected person from source of contamination. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention if any discomfort continues. Place unconscious person on their side in the recovery position and ensure breathing can take place.
<b>Ingestion</b>	DO NOT induce vomiting. Get medical attention immediately. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing.
<b>Skin contact</b>	Remove affected person from source of contamination. Remove contaminated clothing immediately and wash skin with soap and water.
<b>Eye contact</b>	Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes and get medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

<b>General information</b>	Get medical attention promptly if symptoms occur after washing.
----------------------------	---

#### 4.3. Indication of any immediate medical attention and special treatment needed

<b>Notes for the doctor</b>	No specific recommendations.
-----------------------------	------------------------------

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

<b>Suitable extinguishing media</b>	Extinguish with foam, carbon dioxide, dry powder or water fog. Do not use water jet as an extinguisher, as this will spread the fire.
-------------------------------------	---

#### 5.2. Special hazards arising from the substance or mixture

<b>Specific hazards</b>	The product is non-combustible. Toxic and corrosive gases or vapours.
-------------------------	---

## 145/W449 - TENNIS COURT PAINT & DRIVE PAINT - ALL COLOURS

### 5.3. Advice for firefighters

**Protective actions during firefighting** Avoid breathing fire gases or vapours. Avoid the spillage or runoff entering drains, sewers or watercourses. Cool containers exposed to flames with water until well after the fire is out.

**Special protective equipment for firefighters** Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions** Avoid inhalation of vapours and contact with skin and eyes. Provide adequate ventilation. Wear protective clothing as described in Section 8 of this safety data sheet.

### 6.2. Environmental precautions

**Environmental precautions** Avoid discharge into drains or watercourses or onto the ground. Contain spillage with sand, earth or other suitable non-combustible material. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body.

### 6.3. Methods and material for containment and cleaning up

**Methods for cleaning up** Avoid the spillage or runoff entering drains, sewers or watercourses. Absorb in vermiculite, dry sand or earth and place into containers. Collect and place in suitable waste disposal containers and seal securely. For waste disposal, see Section 13.

### 6.4. Reference to other sections

**Reference to other sections** For personal protection, see Section 8.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

**Usage precautions** Keep away from heat, sparks and open flame. Avoid spilling. Avoid contact with skin and eyes. Avoid inhalation of vapours and spray mists. Do not eat, drink or smoke when using the product. Good personal hygiene procedures should be implemented. Wash hands and any other contaminated areas of the body with soap and water before leaving the work site. The Manual Handling Operations Regulations may apply to the handling of containers of this product. To assist employers, the following method of calculating the weight for any pack size is given. Take the pack size volume in litres and multiply this figure by the specific gravity value given in section 9. This will give the net weight of the coating in kilograms. Allowance will then have to be made for the immediate packaging to give an approximate gross weight.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage precautions** Store in closed original container at temperatures between 5°C and 25°C. Keep away from heat, sparks and open flame. Protect from freezing and direct sunlight. Keep container tightly closed. Keep containers upright. Store away from the following materials: Oxidising materials. Alkalis. Acids.

### 7.3. Specific end use(s)

**Specific end use(s)** The identified uses for this product are detailed in Section 1.2.

**Usage description** Collect and place in suitable waste disposal containers and seal securely. Label the containers containing waste and contaminated materials and remove from the area as soon as possible.

## SECTION 8: Exposure Controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limits

## 145/W449 - TENNIS COURT PAINT & DRIVE PAINT - ALL COLOURS

### Calcium Carbonate

Long-term exposure limit (8-hour TWA): WEL 10 mg/m<sup>3</sup> inhalable dust

Long-term exposure limit (8-hour TWA): WEL 4 mg/m<sup>3</sup> respirable dust

### Diatomaceous Earth

Long-term exposure limit (8-hour TWA): WEL 1.2 mg/m<sup>3</sup> respirable dust

### Monopropylene glycol

Long-term exposure limit (8-hour TWA): WEL 150 ppm 10 mg/m<sup>3</sup>

### Calcium Magnesium Carbonate

Long-term exposure limit (8-hour TWA): WEL 4 mg/m<sup>3</sup> resp.dust

### Hydroxyethyl cellulose

Long-term exposure limit (8-hour TWA): WEL 10 mg/m<sup>3</sup> total dust

Short-term exposure limit (15-minute): WEL 4 mg/m<sup>3</sup> resp.dust

### AMMONIA ...%

Long-term exposure limit (8-hour TWA): WEL 25 ppm 35 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 17 ppm 24 mg/m<sup>3</sup>

WEL = Workplace Exposure Limit

### Monopropylene glycol (CAS: 57-55-6)

<b>DNEL</b>	Industry/Professional - Inhalation; Long term systemic effects: 50 mg/m <sup>3</sup> Industry/Professional - Inhalation; Long term local effects: 10 mg/m <sup>3</sup> Consumer - Inhalation; Long term systemic effects: 168 mg/m <sup>3</sup> Consumer - Inhalation; Long term local effects: 10 mg/m <sup>3</sup>
<b>PNEC</b>	- Fresh water; 260 mg/l - Marine water; 26 mg/l - Sediment (Freshwater); 572 mg/l - Sediment (Marinewater); 57.2 mg/l - Soil; 50 mg/kg - STP; 20000 mg/l

### 2,2,4 Trimethyl 1,3 Pentanediol Monoisobutyrate (CAS: 25265-77-4)

<b>DNEL</b>	Professional - Inhalation; Long term : 49 mg/m <sup>3</sup> Consumer - Dermal; Long term : 8.3 mg/kg/day Professional - Dermal; Long term : 13.9 mg/kg/day Consumer - Inhalation; Long term : 14.5 mg/m <sup>3</sup> - Oral; Long term : 8.3 mg/kg/day
<b>PNEC</b>	- Soil; 0.13 mg/kg - Fresh water; 0.015 mg/l - Sediment (Marinewater); 0.017 mg/kg - Intermittent release; 0.15 mg/l - Marine water; 0.0015 mg/l - STP; 7.5 mg/l - Sediment (Freshwater); 0.17 mg/kg

### Sodium Benzoate (CAS: 532-32-1)

## 145/W449 - TENNIS COURT PAINT & DRIVE PAINT - ALL COLOURS

### DNEL

Industry - Dermal; Long term systemic effects: 34.7 mg/kg/day  
 Consumer - Oral; Long term systemic effects: 25 mg/kg/day  
 Industry - Inhalation; Long term systemic effects: 10.4 mg/kg/day  
 Consumer - Dermal; Long term systemic effects: 20.8 mg/kg/day  
 Industry - Inhalation; Long term local effects: 6.3 mg/m<sup>3</sup>  
 Consumer - Inhalation; Long term systemic effects: 2.1 mg/m<sup>3</sup>  
 Consumer - Inhalation; Long term local effects: 1.3 mg/m<sup>3</sup>

### 8.2. Exposure controls

#### Protective equipment



#### Appropriate engineering controls

Provide adequate ventilation. Observe Occupational Exposure Limits and minimise the risk of inhalation of vapours.

#### Eye/face protection

Wear approved, tight fitting safety glasses where splashing is probable.

#### Hand protection

Wear protective gloves made of the following material: Neoprene, nitrile, polyethylene or PVC. It should be noted that liquid may penetrate the gloves. Frequent changes are recommended. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. Barrier cream applied before work may make it easier to clean the skin after exposure, but does not prevent absorption through the skin.

#### Other skin and body protection

Wear appropriate clothing to prevent reasonably probable skin contact.

#### Hygiene measures

No specific hygiene procedures recommended but good personal hygiene practices should always be observed when working with chemical products.

#### Respiratory protection

Protection against nuisance dust must be used when the airborne concentration exceeds 10 mg/m<sup>3</sup>. In case of inadequate ventilation or risk of inhalation of dust, use suitable respiratory equipment with particle filter (type P2).

### SECTION 9: Physical and Chemical Properties

#### 9.1. Information on basic physical and chemical properties

Appearance	Viscous liquid. Coloured liquid.
Colour	Red. Green. Various colours
Odour	Mild.
Relative density	1.2 - 1.3 @ @ 20 C°C
Solubility(ies)	Miscible with water
Viscosity	2.5 (Rotothinner) P @ 25 C°C

#### 9.2. Other information

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

##### Reactivity

There are no known reactivity hazards associated with this product.

#### 10.2. Chemical stability

##### Stability

Stable at normal ambient temperatures and when used as recommended.

## 145/W449 - TENNIS COURT PAINT & DRIVE PAINT - ALL COLOURS

### 10.3. Possibility of hazardous reactions

**Possibility of hazardous reactions** Not determined.

### 10.4. Conditions to avoid

**Conditions to avoid** Avoid heat, flames and other sources of ignition. Avoid contact with the following materials: Acids. Oxidising agents.

### 10.5. Incompatible materials

**Materials to avoid** Strong alkalis. Strong acids. Strong oxidising agents.

### 10.6. Hazardous decomposition products

**Hazardous decomposition products** Oxides of carbon. Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

**Toxicological effects** No data recorded.

**General information** No specific health hazards known.

**Inhalation** No specific health hazards known.

**Ingestion** No harmful effects expected from quantities likely to be ingested by accident.

**Skin contact** Prolonged contact may cause dryness of the skin.

**Eye contact** May cause temporary eye irritation.

**Acute and chronic health hazards** This product has low toxicity. Only large quantities are likely to have adverse effects on human health.

**Route of entry** Skin absorption. Ingestion. Skin and/or eye contact.

**Medical considerations** Skin disorders and allergies.

**Toxicological information**

## SECTION 12: Ecological Information

**Ecotoxicity** There are no data on the ecotoxicity of this product.

### 12.1. Toxicity

### 12.2. Persistence and degradability

**Persistence and degradability** The product is expected to be biodegradable.

### 12.3. Bioaccumulative potential

**Bioaccumulative potential** No data available on bioaccumulation.

### 12.4. Mobility in soil

**Mobility** The product contains substances, which are water soluble and may spread in water systems.

### 12.5. Results of PBT and vPvB assessment

### 12.6. Other adverse effects

**Other adverse effects** Not determined.

## 145/W449 - TENNIS COURT PAINT & DRIVE PAINT - ALL COLOURS

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

<b>General information</b>	Avoid the spillage or runoff entering drains, sewers or watercourses. Waste should be treated as controlled waste. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.
<b>Disposal methods</b>	Avoid the spillage or runoff entering drains, sewers or watercourses.
<b>Waste class</b>	When this coating, in its liquid state, as supplied, becomes a waste, it is categorised as non-hazardous waste, with code 08 01 12 (WATER BASED LIQUID WASTE). Part used containers, not drained and/or rigorously scraped out and containing dry residues of the supplied coating, are categorised as non-hazardous waste, with code 08 01 12 (WATER BASED LIQUID WASTE). If mixed with other wastes, the above waste code may not be applicable. Used containers, drained and/or rigorously scraped out and containing dry residues of the supplied coating, are categorised as non-hazardous waste, with code 15 01 02 (plastic packaging) or 15 01 04 (metal packaging).

### SECTION 14: Transport information

<b>General</b>	The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).
----------------	--

#### 14.1. UN number

Not applicable.

#### 14.2. UN proper shipping name

Not applicable.

**Proper shipping name (ADR/RID)** PAINT OR PAINT RELATED MATERIAL

**Proper shipping name (IMDG)** PAINT OR PAINT RELATED MATERIAL

**Proper shipping name (ICAO)** PAINT OR PAINT RELATED MATERIAL

**Proper shipping name (ADN)** PAINT OR PAINT RELATED MATERIAL

#### 14.3. Transport hazard class(es)

Not applicable.

#### 14.4. Packing group

Not applicable.

#### 14.5. Environmental hazards

**Environmentally hazardous substance/marine pollutant**

No.

#### 14.6. Special precautions for user

No information required.

#### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

**Transport in bulk according to** Not applicable.

**Annex II of MARPOL 73/78 and the IBC Code**

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

## 145/W449 - TENNIS COURT PAINT & DRIVE PAINT - ALL COLOURS

<b>National regulations</b>	The Control of Substances Hazardous to Health Regulations 2002 (SI 2002 No. 2677) (as amended).
<b>EU legislation</b>	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended). Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).
<b>Guidance</b>	Workplace Exposure Limits EH40.

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

### SECTION 16: Other information

<b>Revision comments</b>	Issued in new format for Reach compliance in accordance with EC 1272/2008 Issued in accordance with Annex II to REACH, as amended by Commission Regulation (EU) No. 453/2010 Amendment to Section 8.2, recommendations for respiratory protective equipment and hand protection.
<b>Issued by</b>	Technical Dept. (P.E.)
<b>Revision date</b>	14/04/2015
<b>Revision</b>	8
<b>Supersedes date</b>	27/11/2012
<b>SDS number</b>	10627
<b>SDS status</b>	Approved.
<b>Signature</b>	Initials _____
<b>Risk phrases in full</b>	Not classified. R34 Causes burns. R35 Causes severe burns. R37 Irritating to respiratory system. R50 Very toxic to aquatic organisms.
<b>Hazard statements in full</b>	H314 Causes severe skin burns and eye damage. H335 May cause respiratory irritation. H400 Very toxic to aquatic life.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.