

# Centrecoat™

Thermoplastic Lines, Shapes and Symbols



Technical Data Sheet

## PRODUCT DESCRIPTION

Centrecoat Thermoplastic is an easy to apply, extremely flexible, preformed road marking material. It is available in a range of colours as 5m rolls (50 – 100 mm widths), 1m long strips and as Numbers, Letters, Logos or Symbols pre-cut from sheets. Ideal for fast permanent installation or re-instatement of road markings, car park markings and cycle ways.

## PROPERTIES

Extremely durable

Quick drying

Complies with New Roads and Streets Act 1991 code of practice for reinstatement

Clean cut, crisp markings that can be trafficked within minutes of application

Can be applied at any time of the year

Resistant to deterioration due to the exposure to sunlight, water, oil, petrol, salt and adverse weather conditions

Reflective glass beads can be applied during application

## RECOMMENDED APPLICATION METHODS

Requires only one person and a gas torch to apply.

Ensure surfaces are clean, dry and sound.

The surface must be dry. Use the gas torch to heat until there is no further colour change, which occurs at the surface during the drying process.

Do not apply on top of paint unless a Primer has been applied.

On concrete and extremely smooth surfaces a Primer must be applied.

## TECHNICAL

Appearance/Form:	Solid tape or sheet
Boiling Point:	NDA
Flash Point:	>230C
Volatility by Volume (%):	-
Specific Gravity (at 25°C):	1.9 0.1 Kg/l
Volatility:	N/A
Solubility/Miscibility in Water:	Insoluble
pH Value:	N/A
Viscosity:	N/A

## COVERAGE

N/A

## AVERAGE DRYING TIMES

Touch dry: 10 minutes.

## RECOMMENDED PRIMERS

Centrecoat Aerosol Tack Coat

## PACKAGING

Store packages flat.

Keep materials dry, clean and avoid impact.

Storage temperature range 5°C to 30°C.