



SAFETY DATA SHEET

131/W221 - PROFLOOR HIGH PERFORMANCE WB PRIMER - BASE

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name 131/W221 - PROFLOOR HIGH PERFORMANCE WB PRIMER - BASE

Product number 131/W221/1 - BASE

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses BASE FOR TWO COMPONENT PRIMER

1.3. Details of the supplier of the safety data sheet

Supplier COO-VAR
Lockwood Street
Hull
HU2 0HN
+44 (0) 1482 328053(T)
+44 (0) 1482 219266(F)
info@coo-var.co.uk

Contact person Technical Department -, 08.30 - 16.30 hrs Mon - Thurs, 08.30 - 15.00 hrs Fri, as above

1.4. Emergency telephone number

Emergency telephone +44 (0) 1482 328053 (08.30 - 16.30 hrs Mon - Thurs, 08.30 - 15.00 hrs Fri)

SDS No. 20179

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified

Health hazards Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317

Environmental hazards Aquatic Chronic 2 - H411

Classification (67/548/EEC or 1999/45/EC) Xi;R36/38. R43. N;R51/53.

Human health The product contains a small amount of sensitising substance. May cause skin sensitisation or allergic reactions in sensitive individuals.

Physicochemical When handled correctly, undamaged units represent no danger.

2.2. Label elements

Pictogram



131/W221 - PROFLOOR HIGH PERFORMANCE WB PRIMER - BASE

Signal word	Warning
Hazard statements	H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H411 Toxic to aquatic life with long lasting effects.
Precautionary statements	P102 Keep out of reach of children. P101 If medical advice is needed, have product container or label at hand. P261 Avoid breathing vapour/ spray. P273 Avoid release to the environment. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P362+P364 Take off contaminated clothing and wash it before reuse. P501 Dispose of contents/ container in accordance with national regulations.
Supplemental label information	EUH205 Contains epoxy constituents. May produce an allergic reaction.
Contains	REACTION PRODUCT : BISPHENOL A-(EPICHLOROHYDRIN):EPOXY RESIN (NUMBER AVERAGE MW<=700), FORMALDEHYDE, OLIGOMERIC REACTION PRODUCTS WITH 1-CHLORO-2,3-EPOXYPROPANE AND PHENOL, OXIRANE, MONO [(C12-14-ALKYLOXY)METHYL] DERIVS
Supplementary precautionary statements	P264 Wash contaminated skin thoroughly after handling. P302+P352 IF ON SKIN: Wash with plenty of water. P332+P313 If skin irritation occurs: Get medical advice/ attention. P337+P313 If eye irritation persists: Get medical advice/ attention. P391 Collect spillage.

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

REACTION PRODUCT : BISPHENOL A-(EPICHLOROHYDRIN):EPOXY RESIN (NUMBER AVERAGE MW<=700)		60-100%
CAS number: 25068-38-6	EC number: 500-033-5	REACH registration number: 01-2119456619-26-0006
Classification	Classification (67/548/EEC or 1999/45/EC)	
Skin Irrit. 2 - H315	R43 Xi;R36/38 N;R51/53	
Eye Irrit. 2 - H319		
Skin Sens. 1 - H317		
Aquatic Chronic 2 - H411		

131/W221 - PROFLOOR HIGH PERFORMANCE WB PRIMER - BASE

FORMALDEHYDE, OLIGOMERIC REACTION PRODUCTS WITH 1-CHLORO-2,3-EPOXYPROPANE AND PHENOL		10-30%
CAS number: 9003-36-5	EC number: 500-006-8	REACH registration number: 01-2119454392-40-0003
Classification Skin Irrit. 2 - H315 Skin Sens. 1 - H317 Aquatic Chronic 2 - H411	Classification (67/548/EEC or 1999/45/EC) Xi;R38. N;R51/53. R43.	
OXIRANE, MONO [(C12-14- ALKYL OXY)METHYL] DERIVS		10-30%
CAS number: 68609-97-2	REACH registration number: 01-2119485289-22-0005	
Classification Skin Irrit. 2 - H315 Skin Sens. 1 - H317	Classification (67/548/EEC or 1999/45/EC) R43 Xi;R38	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Never give anything by mouth to an unconscious person.
Inhalation	Remove affected person from source of contamination. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention if any discomfort continues. Place unconscious person on their side in the recovery position and ensure breathing can take place.
Ingestion	Give a few small glasses of water or milk to drink. Never give anything by mouth to an unconscious person. Do not induce vomiting. Get medical attention if any discomfort continues.
Skin contact	Remove affected person from source of contamination. Rinse immediately with plenty of water. Remove contaminated clothing. Get medical attention if irritation persists after washing.
Eye contact	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Get medical attention immediately. Continue to rinse.

4.2. Most important symptoms and effects, both acute and delayed

General information	Get medical attention promptly if symptoms occur after washing.
----------------------------	---

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	No specific recommendations. If in doubt, get medical attention promptly.
-----------------------------	---

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Non flammable at room temperature, but will burn. Use fire-extinguishing media suitable for the surrounding fire. Extinguish with the following media: Water spray, fog or mist. Foam, carbon dioxide or dry powder.
-------------------------------------	--

5.2. Special hazards arising from the substance or mixture

131/W221 - PROFLOOR HIGH PERFORMANCE WB PRIMER - BASE

Specific hazards Toxic gases or vapours.

5.3. Advice for firefighters

Protective actions during firefighting Avoid breathing fire gases or vapours. Containers close to fire should be removed or cooled with water.

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid inhalation of vapours and contact with skin and eyes. Provide adequate ventilation. Wear protective clothing as described in Section 8 of this safety data sheet.

6.2. Environmental precautions

Environmental precautions Avoid discharge into drains or watercourses or onto the ground. Contain spillage with sand, earth or other suitable non-combustible material. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Avoid the spillage or runoff entering drains, sewers or watercourses. Absorb in vermiculite, dry sand or earth and place into containers. Collect and place in suitable waste disposal containers and seal securely. For waste disposal, see Section 13.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Avoid inhalation of vapours. Avoid spilling. Avoid contact with skin and eyes. Do not eat, drink or smoke when using the product. Good personal hygiene procedures should be implemented. Wash hands and any other contaminated areas of the body with soap and water before leaving the work site. The Manual Handling Operations Regulations may apply to the handling of containers of this product. For products sold by weight refer to the guide net weight indicated on the container. Allowance will have to be made for the immediate packaging to give an approximate gross weight.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly closed original container in a dry, cool and well-ventilated place. Store in closed original container at temperatures between 5°C and 25°C. Protect from freezing and direct sunlight. Keep containers upright.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

Usage description Collect and place in suitable waste disposal containers and seal securely. Label the containers containing waste and contaminated materials and remove from the area as soon as possible.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

131/W221 - PROFLOOR HIGH PERFORMANCE WB PRIMER - BASE

REACTION PRODUCT : BISPHENOL A-(EPICHLOROHYDRIN):EPOXY RESIN (NUMBER AVERAGE MW<=700) (CAS: 25068-38-6)

DNEL

Workers - Dermal; Short term systemic effects: 8.33 mg/kg/day
 Workers - Inhalation; Long term systemic effects: 12.25 mg/m³
 Workers - Dermal; Long term systemic effects: 8.33 mg/kg/day
 Workers - Inhalation; Short term systemic effects: 12.25 mg/m³
 Consumer - Oral; Long term systemic effects: 0.75 mg/kg/day
 Consumer - Oral; Short term systemic effects: 0.75 mg/kg/day
 Consumer - Dermal; Long term systemic effects: 3.571 mg/kg/day

PNEC

- Fresh water; Long term 0.006 mg/l
- Sediment (Freshwater); Long term 0.996 mg/l
- STP; Long term 10 mg/l
- Soil; Long term 0.196 mg/l
- Marine water; 0.0006 mg/l
- Sediment (Marinewater); 0.0996 mg/l
- Water; 0.0018 mg/l

FORMALDEHYDE, OLIGOMERIC REACTION PRODUCTS WITH 1-CHLORO-2,3-EPOXYPROPANE AND PHENOL (CAS: 9003-36-5)

DNEL

Workers - Inhalation; Long term systemic effects: 29.39 mg/kg
 Workers - Dermal; Long term systemic effects: 104.15 mg/kg/day
 General population - Inhalation; Long term systemic effects: 8.7 mg/kg
 General population - Dermal; Long term systemic effects: 62.5 mg/kg/day
 General population - Oral; Long term systemic effects: 6.25 mg/kg/day

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate ventilation. Avoid inhalation of vapours. Observe any occupational exposure limits for the product or ingredients.

Personal protection

Unprotected persons should be kept away from treated areas.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles.

Hand protection

To protect hands from chemicals, gloves should comply with European Standards EN388 and 374. As a general principle, exposure should be managed by means other than the provision of protective gloves. Manufacturer's performance data suggest that the optimum glove for use should be: Butyl rubber. Thickness: > 0.5 mm Permeation breakthrough time according to EN374 - class: (1-6) e.g. minimum 480 mins. or Nitrile rubber. Thickness: > 0.4 mm Permeation breakthrough time according to EN374 - class: (1-6) e.g. minimum 240 mins. Caution: The performance of gloves under actual working conditions can be significantly affected by many factors and the information provided according to EN374 may not accord with what is achieved in practice. We recommend that expert professional advice is sought that takes into account of the work processes and working environment applicable for each task where gloves are to be worn.

Other skin and body protection

Wear appropriate clothing to prevent reasonably probable skin contact.

131/W221 - PROFLOOR HIGH PERFORMANCE WB PRIMER - BASE

Hygiene measures	Use engineering controls to reduce air contamination to permissible exposure level. No specific hygiene procedures recommended but good personal hygiene practices should always be observed when working with chemical products.
Respiratory protection	No specific recommendations. Respiratory protection may be required if excessive airborne contamination occurs.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Viscous liquid.
Colour	Light (or pale). Yellow.
Odour	Almost odourless.
Initial boiling point and range	>200°C @ 760 mm Hg
Flash point	>100°C CC (Closed cup).
Relative density	1.12 @ @ 20 C°C
Solubility(ies)	Insoluble in water
Viscosity	1300 mPas @ 25 C°C

9.2. Other information

Volatile organic compound	This product contains a maximum VOC content of 0 g/litre.
----------------------------------	---

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	There are no known reactivity hazards associated with this product.
-------------------	---

10.2. Chemical stability

Stability	Stable at normal ambient temperatures and when used as recommended.
------------------	---

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	Will not occur
---	----------------

10.4. Conditions to avoid

Conditions to avoid	Not known.
----------------------------	------------

10.5. Incompatible materials

Materials to avoid	Strong acids. Alkalis - inorganic. Amines. Mercaptans (thiols).
---------------------------	---

10.6. Hazardous decomposition products

Hazardous decomposition products	Oxides of carbon. Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.
---	--

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological effects	No data recorded.
General information	No specific health hazards known.
Inhalation	May cause respiratory system irritation.

131/W221 - PROFLOOR HIGH PERFORMANCE WB PRIMER - BASE

Ingestion	Harmful if swallowed. Ingestion may cause severe irritation of the mouth, the oesophagus and the gastrointestinal tract.
Skin contact	Irritating to skin. May cause sensitisation by skin contact.
Eye contact	Irritating to eyes.
Acute and chronic health hazards	May cause sensitisation by skin contact. Delayed appearance of the complaints and development of hypersensitivity (difficulty breathing, coughing, asthma) are possible.
Route of entry	Inhalation Skin absorption. Ingestion. Skin and/or eye contact.
Medical considerations	Skin disorders and allergies.
Toxicological information	

SECTION 12: Ecological Information

Ecotoxicity There are no data on the ecotoxicity of this product.

12.1. Toxicity

12.2. Persistence and degradability

Persistence and degradability No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

12.4. Mobility in soil

Mobility The product is non-volatile.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects Not determined.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Avoid the spillage or runoff entering drains, sewers or watercourses. Waste should be treated as controlled waste. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. When handling waste, the safety precautions applying to handling of the product should be considered. DO NOT reuse containers containing residual product without commercial cleaning

Waste class When this material, in its liquid state, as supplied, becomes a waste, it is categorised as a hazardous waste, with code 08 01 11* (EPOXY BASED LIQUID WASTE). Part-used containers, not drained and/or rigorously scraped out and containing residues of the supplied material, are categorised as hazardous waste, with code 08 01 11* (EPOXY BASED LIQUID WASTE). Ideally this component should be mixed with the appropriate hardener and allowed to react fully to produce a solid waste. Neutralised empty packages, are categorised as non-hazardous waste, with code 15 01 02(plastic packaging) or 15 01 04 (metal packaging)

SECTION 14: Transport information

General This product is packed in accordance with the Limited Quantity Provisions of CDGCPL2, ADR and IMDG.

131/W221 - PROFLOOR HIGH PERFORMANCE WB PRIMER - BASE

14.1. UN number

UN No. (ADR/RID) 3082

UN No. (IMDG) 3082

14.2. UN proper shipping name

Proper shipping name (ADR/RID) PAINT OR PAINT RELATED MATERIAL

Proper shipping name (IMDG) PAINT OR PAINT RELATED MATERIAL

Proper shipping name (ICAO) PAINT OR PAINT RELATED MATERIAL

Proper shipping name (ADN) PAINT OR PAINT RELATED MATERIAL

14.3. Transport hazard class(es)

ADR/RID class 9

ADR/RID subsidiary risk HAZARD ID 90

IMDG class 9

ICAO class/division 9

Transport labels



14.4. Packing group

ADR/RID packing group III

IMDG packing group III

ICAO packing group III

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



14.6. Special precautions for user

EmS F-A S-F

Tunnel restriction code (E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

Annex II of MARPOL 73/78 and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716).

131/W221 - PROFLOOR HIGH PERFORMANCE WB PRIMER - BASE

EU legislation	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended). Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).
Guidance	Workplace Exposure Limits EH40. CHIP for everyone HSG228. Safety Data Sheets for Substances and Preparations. Approved Classification and Labelling Guide (Sixth edition) L131. Dangerous Substances and Explosive Atmospheres Regulations 2002 [L138]

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Revision comments	Issued in new format for Reach compliance in accordance with EC 1272/2008 Issued in accordance with Annex II to REACH, as amended by Commission Regulation (EU) No. 453/2010 Amendment to Section 8.2, recommendations for respiratory protective equipment and hand protection.
Issued by	Technical Dept. (P.E.)
Revision date	31/05/2017
Revision	6
Supersedes date	23/01/2015
SDS number	10808
SDS status	Approved.
Risk phrases in full	R36/38 Irritating to eyes and skin. R38 Irritating to skin. R43 May cause sensitisation by skin contact. R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Hazard statements in full	H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H411 Toxic to aquatic life with long lasting effects.
Signature	Initials _____

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.