

COO-VAR®

PAINTS, PRIMERS AND SPECIALISED COATINGS

SAFETY DATA SHEET

206/Q607 - GRAFFITI REMOVER - AEROSOL

According to Regulation (EC) No 1907/2006, Annex II, as amended by Regulation (EU) No 453/2010

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name 206/Q607 - GRAFFITI REMOVER - AEROSOL
Product number 206/Q607/1

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Cleaning agent.

1.3. Details of the supplier of the safety data sheet

Supplier COO-VAR
 Lockwood Street
 Hull
 HU2 0HN
 +44 (0) 1482 328053(T)
 +44 (0) 1482 219266(F)
 info@coo-var.co.uk

Contact person Technical Department -, 08.30 - 16.30 hrs Mon - Thurs, 08.30 - 15.00 hrs Fri, as above

1.4. Emergency telephone number

Emergency telephone +44 (0) 1482 328053 (08.30 - 16.30 hrs Mon - Thurs, 08.30 - 15.00 hrs Fri)

SDS No. 10765

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Aerosol 1 - H222, H229
Health hazards Eye Irrit. 2 - H319 STOT SE 3 - H336
Environmental hazards Not Classified

2.2. Label elements

Pictogram



Signal word Danger

Hazard statements H222 Extremely flammable aerosol.
 H229 Pressurised container: may burst if heated.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.

206/Q607 - GRAFFITI REMOVER - AEROSOL

Precautionary statements	<p>P102 Keep out of reach of children.</p> <p>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</p> <p>P211 Do not spray on an open flame or other ignition source.</p> <p>P251 Do not pierce or burn, even after use.</p> <p>P271 Use only outdoors or in a well-ventilated area.</p> <p>P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.</p> <p>P501 Dispose of contents/ container in accordance with national regulations.</p>
Contains	1-METHOXY-2-PROPANOL, HYDROCARBONS, C9-C11, <2% AROMATICS
Supplementary precautionary statements	<p>P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.</p> <p>P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P312 Call a POISON CENTRE/doctor if you feel unwell.</p> <p>P337+P313 If eye irritation persists: Get medical advice/ attention.</p>
Detergent Labelling	>= aliphatic hydrocarbons. < 5% non-ionic surfactants

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB. In use may form flammable/explosive vapour-air mixture.

SECTION 3: Composition/information on ingredients**3.2. Mixtures**

1-METHOXY-2-PROPANOL	30-60%
CAS number: 107-98-2	EC number: 203-539-1
	REACH registration number: 01-2119457435-35-0000
Classification	Classification (67/548/EEC or 1999/45/EC)
Flam. Liq. 3 - H226	R10 R67
STOT SE 3 - H336	
PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS	10-30%
CAS number: 68476-85-7	EC number: 270-704-2
Classification	Classification (67/548/EEC or 1999/45/EC)
Flam. Gas 1 - H220	F+;R12 Carc. Cat. 1;R45 Muta. Cat. 2;R46
Press. Gas (Liq.) - H280	
HYDROCARBONS, C9-C11, <2% AROMATICS	10-30%
CAS number: —	EC number: 919-857-5
	REACH registration number: 01-2119463258-33-XXXX
Classification	Classification (67/548/EEC or 1999/45/EC)
Flam. Liq. 3 - H226	Xn;R65. R10,R66,R67.
STOT SE 3 - H336	
Asp. Tox. 1 - H304	

206/Q607 - GRAFFITI REMOVER - AEROSOL

Dimethyl succinate		1-5%
CAS number: 106-65-0	EC number: 203-419-9	REACH registration number: 01-2119486681-29-0000
Classification		
Eye Irrit. 2 - H319		
C9-C11 Alcohol ethoxylate		1-5%
CAS number: 68439-46-3		
Classification		Classification (67/548/EEC or 1999/45/EC)
Acute Tox. 4 - H302		Xn;R22. Xi;R41.
Eye Dam. 1 - H318		

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

Composition comments CAS 68476-65-7 Petroleum gases - as a substance contains less than 0.1%w/w 1,3-butadiene the fully harmonised classification regarding Muta. 1B H340 and Carc. 1A H350 does not apply.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	Move affected person to fresh air at once.
Inhalation	Move affected person to fresh air at once. If breathing stops, provide artificial respiration. Keep affected person warm and at rest. Get medical attention immediately.
Ingestion	Rinse mouth thoroughly with water. Do not induce vomiting. Get medical attention if any discomfort continues.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. Get medical attention if any discomfort continues.
Eye contact	Rinse immediately with plenty of water. Continue to rinse for at least 15 minutes. Remove any contact lenses and open eyelids wide apart. Get medical attention if irritation persists after washing.

4.2. Most important symptoms and effects, both acute and delayed

General information	Get medical attention promptly if symptoms occur after washing.
Inhalation	Vapours may cause drowsiness and dizziness.
Ingestion	Drowsiness, dizziness, disorientation, vertigo.
Skin contact	Prolonged skin contact may cause redness and irritation.
Eye contact	May cause severe eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor No specific recommendations.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Water spray, foam, dry powder or carbon dioxide.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.

206/Q607 - GRAFFITI REMOVER - AEROSOL

5.2. Special hazards arising from the substance or mixture

Specific hazards	Pressurised container: Must not be exposed to temperatures above 50 °C. May explode when heated or when exposed to flames or sparks. Vapours are heavier than air and may spread near ground and travel a considerable distance to a source of ignition and flash back.
Hazardous combustion products	Oxides of carbon. Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

5.3. Advice for firefighters

Protective actions during firefighting	Use water spray to reduce vapours. Containers can burst violently or explode when heated, due to excessive pressure build-up. Cool aerosol containers exposed to heat with water spray and remove container, if no risk involved.
Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	Ensure suitable respiratory protection is worn during removal of spillages in confined areas.
-----------------------------	-----------------------------------------------------------------------------------------------

6.2. Environmental precautions

Environmental precautions	Avoid discharge into drains.
----------------------------------	------------------------------

6.3. Methods and material for containment and cleaning up

Methods for cleaning up	Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Absorb in vermiculite, dry sand or earth and place into containers. Provide adequate ventilation. Contain spillage with sand, earth or other suitable non-combustible material. Avoid the spillage or runoff entering drains, sewers or watercourses.
--------------------------------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

6.4. Reference to other sections

Reference to other sections	For personal protection, see Section 8. For waste disposal, see Section 13. See Section 11 for additional information on health hazards.
------------------------------------	------------------------------------------------------------------------------------------------------------------------------------------

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions	Keep away from heat, sparks and open flame. Read and follow manufacturer's recommendations. Avoid inhalation of vapours and spray mists. Do not spray near naked flame or any incandescent material. When sprayed on a naked flame or any incandescent material the aerosol vapours can be ignited.
--------------------------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions	Extremely flammable. Store at moderate temperatures in dry, well ventilated area. Keep away from heat, sparks and open flame. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn even after use.
Storage class	Extremely Flammable Aerosol.

7.3. Specific end use(s)

Specific end use(s)	The identified uses for this product are detailed in Section 1.2.
----------------------------	-------------------------------------------------------------------

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

1-METHOXY-2-PROPANOL

206/Q607 - GRAFFITI REMOVER - AEROSOL

Long-term exposure limit (8-hour TWA): WEL 100 ppm 375 mg/m³

Short-term exposure limit (15-minute): WEL 150 ppm 560 mg/m³

Sk

PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS

Long-term exposure limit (8-hour TWA): WEL 1000 ppm 1750 mg/m³

Short-term exposure limit (15-minute): WEL 1250 ppm 2180 mg/m³

WEL = Workplace Exposure Limit

Sk = Can be absorbed through the skin.

Ingredient comments

SUP = Supplier's recommendation.

1-METHOXY-2-PROPANOL (CAS: 107-98-2)

DNEL

Workers - Inhalation; Short term local effects: 553.5 mg/m³

Workers - Dermal; Long term systemic effects: 183 mg/kg/day

Workers - Inhalation; Long term systemic effects: 369 mg/m³

Consumer - Dermal; Long term systemic effects: 78 mg/kg/day

Consumer - Inhalation; Long term systemic effects: 43.9 mg/m³

Consumer - Oral; Long term systemic effects: 33 mg/kg/day

PNEC

- Fresh water; 10 mg/l

- Marine water; 1 mg/l

- Intermittent release; 100 mg/l

- STP; 100 mg/l

- Sediment (Freshwater); 52.3 mg/kg

- Sediment (Marinewater); 5.2 mg/kg

- Soil; 4.59 mg/kg

HYDROCARBONS, C9-C11, <2% AROMATICS

DNEL

Consumer - Oral; Long term systemic effects: 300 mg/kg/day

Industry - Inhalation; Long term systemic effects: 1500 mg/m³

Industry - Dermal; Long term systemic effects: 300 mg/kg/day

Consumer - Dermal; Long term systemic effects: 300 mg/kg/day

Consumer - Inhalation; Long term systemic effects: 900 mg/m³

PNEC

No PNEC available. Substance is a hydrocarbon UVCB. Standard tests for this endpoint are intended for single substances and are not appropriate for the risk assessment of this complex substance.

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate ventilation. Avoid inhalation of vapours and spray/mists. Observe any occupational exposure limits for the product or ingredients.

Personal protection

When using do not smoke.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles.

206/Q607 - GRAFFITI REMOVER - AEROSOL

Hand protection	To protect hands from chemicals, gloves should comply with European Standards EN388 and 374. As a general principle, exposure should be managed by means other than the provision of protective gloves. Manufacturer's performance data suggest that the optimum glove for use should be: Butyl rubber. Thickness: > 0.3 mm Permeation breakthrough time according to EN374 - class: (1-6) e.g. minimum 480 mins. Caution: The performance of gloves under actual working conditions can be significantly affected by many factors and the information provided according to EN374 may not accord with what is achieved in practice. We recommend that expert professional advice is sought that takes into account of the work processes and working environment applicable for each task where gloves are to be worn.
Other skin and body protection	Wear appropriate clothing to prevent reasonably probable skin contact.
Hygiene measures	When using do not eat, drink or smoke. Wash promptly if skin becomes contaminated.
Respiratory protection	No specific recommendations. Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit. If ventilation is inadequate, suitable respiratory protection must be worn. It is recommended to use respiratory equipment with combination filter, type A2/P2.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Aerosol containing a mixture of active ingredients, solvents and propellants.
Colour	White / off-white.
Odour	Organic solvents.
Odour threshold	Not available.
pH	No information available.
Melting point	No information available.
Initial boiling point and range	No information available.
Flash point	< -40°C
Evaporation rate	No information available.
Evaporation factor	No information available.
Flammability (solid, gas)	Extremely flammable aerosol.
Upper/lower flammability or explosive limits	Lower flammable/explosive limit: 1.8% Upper flammable/explosive limit: 9.5%
Other flammability	No information available.
Vapour pressure	No information available.
Relative density	No information available.
Bulk density	No information available.
Solubility(ies)	Slightly soluble in water.
Auto-ignition temperature	410-580°C
Viscosity	No specific test data are available.
Explosive properties	No specific test data are available.
Comments	Information given is applicable to the major ingredient.

206/Q607 - GRAFFITI REMOVER - AEROSOL

9.2. Other information

Volatile organic compound This product contains a maximum VOC content of 788 g/l.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Under normal conditions of storage and use, no hazardous reactions will occur. Will not polymerise.

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition. Avoid exposing aerosol containers to high temperatures or direct sunlight.

10.5. Incompatible materials

Materials to avoid Strong acids. Strong alkalis. Strong oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition products Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

ATE oral (mg/kg) 20,000.0

Serious eye damage/irritation

Serious eye damage/irritation Causes serious eye irritation.

Respiratory sensitisation

Respiratory sensitisation Based on available data the classification criteria are not met.

Skin sensitisation

Skin sensitisation Based on available data the classification criteria are not met.

Carcinogenicity

Carcinogenicity Based on available data the classification criteria are not met.

Reproductive toxicity

Reproductive toxicity - fertility Based on available data the classification criteria are not met.

Specific target organ toxicity - single exposure

STOT - single exposure Based on available data the classification criteria are not met.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Based on available data the classification criteria are not met.

Aspiration hazard

Aspiration hazard Not anticipated to present an aspiration hazard, based on chemical structure.

206/Q607 - GRAFFITI REMOVER - AEROSOL

General information	The product contains small amounts of organic solvents. Extensive use of the product in areas with inadequate ventilation may result in the accumulation of hazardous vapour concentrations.
Inhalation	High exposures may cause an abnormal heart rhythm and prove suddenly fatal. Very high atmospheric concentrations may cause anaesthetic effects and asphyxiation.
Ingestion	May cause soreness and redness of mouth and throat. May cause nausea, headache, dizziness and intoxication.
Skin contact	Prolonged contact may cause redness, irritation and dry skin.
Eye contact	Irritating to eyes. Vapour or spray in the eyes may cause irritation and smarting. Repeated exposure may cause chronic eye irritation.
Acute and chronic health hazards	Prolonged and repeated contact with solvents over a long period may lead to permanent health problems. Irritating to eyes.
Route of exposure	Inhalation Ingestion
Target organs	Central nervous system Skin Respiratory system, lungs
Medical symptoms	Irritation of eyes and mucous membranes.
Toxicological information	
1414	

SECTION 12: Ecological Information

Ecotoxicity The product components are not classified as environmentally hazardous. However, large or frequent spills may have hazardous effects on the environment.

12.1. Toxicity

Toxicity Not regarded as dangerous for the environment.

12.2. Persistence and degradability

Persistence and degradability Biodegradable in part only.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

12.4. Mobility in soil

Mobility The product is soluble in water.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment Not determined.

12.6. Other adverse effects

Other adverse effects None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Do not puncture or incinerate even when empty.

Disposal methods Containers should be thoroughly emptied before disposal because of the risk of an explosion. Do not puncture or incinerate, even when empty. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

206/Q607 - GRAFFITI REMOVER - AEROSOL

Waste class Empty Aerosol: 15 01 10 (Containing hazardous residues). Full or Partially Empty Aerosol: 16 05 04. Empty Aerosol: 15 01 04 (No hazardous residues).

SECTION 14: Transport information

General This product is packed in accordance with the Limited Quantity Provisions of CDGCPL2, ADR and IMDG. These provisions allow transport of aerosols of less than 1 litre packed in cartons of less than 30kg gross weight to be exempt from control providing that they are labelled in accordance with the requirements of these regulations to show that they are being transported as Limited Quantities. Aerosols not so packed and labelled must show the following.

14.1. UN number

UN No. (ADR/RID)	1950
UN No. (IMDG)	1950
UN No. (ICAO)	1950
UN No. (ADN)	1950

14.2. UN proper shipping name

Proper shipping name (ADR/RID)	AEROSOLS
Proper shipping name (IMDG)	AEROSOLS
Proper shipping name (ICAO)	AEROSOLS
Proper shipping name (ADN)	AEROSOLS

14.3. Transport hazard class(es)

ADR/RID class	2.1
ADR/RID classification code	5F
ADR/RID label	2.1
IMDG class	2.1
ICAO class/division	2.1
ADN class	2.1

Transport labels



14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant
No.

14.6. Special precautions for user

EmS	F-D, S-U
ADR transport category	2
Tunnel restriction code	(D)

206/Q607 - GRAFFITI REMOVER - AEROSOL

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations	The Aerosol Dispensers Regulations 2009 (SI 2009 No. 2824).
EU legislation	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended). Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).
Authorisations (Title VII Regulation 1907/2006)	No specific authorisations are known for this product.
Restrictions (Title VIII Regulation 1907/2006)	No specific restrictions on use are known for this product.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Revision comments	Issued in new format for Reach compliance in accordance with EC 1272/2008 Issued in accordance with Annex II to REACH, as amended by Commission Regulation (EU) No. 453/2010 Changes to composition information.
Issued by	Technical Dept. (P.E.)
Revision date	27/10/2017
Revision	9
Supersedes date	27/07/2017
SDS number	10765
SDS status	Approved.
Hazard statements in full	H220 Extremely flammable gas. H222 Extremely flammable aerosol. H226 Flammable liquid and vapour. H229 Pressurised container: may burst if heated. H280 Contains gas under pressure; may explode if heated. H302 Harmful if swallowed. H304 May be fatal if swallowed and enters airways. H318 Causes serious eye damage. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.
Signature	Initials_____

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.