

LIQUID AEROSOL GRAFFITI REMOVER

206/Q607/1

DESCRIPTION:

Coo-Var Liquid Aerosol Graffiti Remover is an easy to use liquid aerosol graffiti remover.

RECOMMENDED USE:

Coo-Var Liquid Aerosol Graffiti Remover is used to remove graffiti from Coo-Var WB101 and P101 anti-graffiti coatings, for other anti graffiti systems please test first. Tough on graffiti on a range of surfaces. It can also be used for the rapid and efficient removal of marks such as ink, crayon etc from hard, non-porous surfaces.

AVAILABILITY:

400ml aerosol

FINISH:

N/A

COLOUR:

N/A

TYPICAL S.G. (SPECIFIC GRAVITY):

N/A

VOLUME SOLIDS:

N/A

WET FILM THICKNESS W.F.T

N/A

DRY FILM THICKNESS D.F.T

N/A

EXPECTED SPREADING RATE:

N/A

N/A

The practical spreading rate may be lower as this depends on factors such as the porosity and roughness of the surface to be painted and material losses during application.

TYPICAL VISCOSITY:

Liquid

FLASH POINT:

Extremely Flammable

DRYING TIME: @ RECOMMENDED D.F.T

Touch dry: N/A

Hard dry: N/A

Full hardness: N/A

Low temperature and high humidity will adversely affect application, drying and performance of any coating.

MINIMUM OVERCOATING TIME:

N/A

APPLICATION SPECIAL CONDITIONS:

N/A

VOC CONTENT:

N/A

VOC's (Volatile Organic Compounds) contribute to atmospheric pollution

APPLICATION DETAILS:

Application N/A
restrictions

Method: Aerosol

Thinner N/A
(Max vol):

Nozzle size: N/A

Nozzle N/A
pressure:

Cleaning N/A
solvent:

Recoat N/A
interval:

SURFACE PREPARATION:

Hold upright 25 to 30 cm from the surface to be cleaned. Spray thoroughly and wipe clean with a soft, damp cloth or wash away with water.

For further advice contact Coo-Var Technical Services on +44(0)1482 328053

The physical constants are subject to normal manufacturing tolerances.

"COVERING OUR CUSTOMERS' NEEDS SINCE 1908"

LIQUID AEROSOL GRAFFITI REMOVER**206/Q607/1**

MIXING INSTRUCTIONS:

Shake can well before use.

APPLICATION CONDITIONS:

N/A

PRECEDING COAT:

N/A

SUBSEQUENT COAT:

Further applications maybe required for tough marks and stains.

REMARKS:

N.B. It is advisable to test a small inconspicuous area prior to use as some delicate surfaces may be softened.

HEALTH AND SAFETY:

See safety data sheet - SDS 10627

ISSUED:

20 November 2009

REVISION:

0

The information given in this data sheet is based on experience and is accurate to the best of our knowledge. No guarantee should be implied, however, as the conditions of use are beyond our control. This data sheet does not constitute a specification. In case of doubt as to the suitability of the product please contact our Technical Service Department on 01482 328053.

For further advice contact Coo-Var Technical Services on +44(0)1482 328053

The physical constants are subject to normal manufacturing tolerances.

"COVERING OUR CUSTOMERS' NEEDS SINCE 1908"

Ellenshaw Works
Lockwood Street, Hull HU2 0HN
Tel.: +44(0)1482 328053. Fax: +44(0)1482 219266

COO-var
Email: info@coo-var.co.uk
www.coo-var.co.uk