

**Section 1: Identification of the substance/mixture and of the company/undertaking**

**1.1. Product identifier**

**Product name:** FLOOR PAINT

**Product code:** DP5

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

**Use of substance / mixture:** PC9a: Coatings and paints, thinners, paint removers.

**1.3. Details of the supplier of the safety data sheet**

**Company name:** Bradite Paints  
Ogwen Valley Works  
Bethesda  
Gwynedd  
LL57 4YP  
United Kingdom

**Tel:** +44 (0)1248 600315

**Fax:** +44 (0)1248 602782

**Email:** [sales@bradite.com](mailto:sales@bradite.com)

**1.4. Emergency telephone number**

**Emergency tel:** +44 (0)1248 600315  
(office hours only)

**Section 2: Hazards identification**

**2.1. Classification of the substance or mixture**

**Classification under CLP:** Flam. Liq. 3: H226; Asp. Tox. 1: H304; -: EUH208

**Most important adverse effects:** Contains 2-butanone oxime, cobalt bis(2-ethylhexanoate). May produce an allergic reaction. Flammable liquid and vapour. May be fatal if swallowed and enters airways.

**2.2. Label elements**

**Label elements:**

**Hazard statements:** EUH208: Contains 2-butanone oxime, cobalt bis(2-ethylhexanoate). May produce an allergic reaction.

H226: Flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

**Signal words:** Danger

**Hazard pictograms:** GHS02: Flame

GHS08: Health hazard

# SAFETY DATA SHEET

## FLOOR PAINT

Page: 2



**Precautionary statements:** P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P241: Use explosion-proof electrical/ventilating/lighting/.. equipment.  
P280: Wear protective gloves/protective clothing/eye protection/face protection.  
P301+310: IF SWALLOWED: Immediately call a POISON CENTER/doctor/.  
P303+361+353: IF ON SKIN (or hair): Take off immediately all contaminated clothing.  
Rinse skin with water/shower.  
P331: Do NOT induce vomiting.

### 2.3. Other hazards

**Other hazards:** Not applicable.

**PBT:** This product is not identified as a PBT/vPvB substance.

## Section 3: Composition/information on ingredients

### 3.2. Mixtures

#### Hazardous ingredients:

LOW BOILING POINT HYDROGEN TREATED NAPHTHA - NAPHTHA (PETROLEUM), HYDROTREATED HEAVY - REACH registered number(s): 01-2119463258-33-XXXX

EINECS	CAS	PBT / WEL	CLP Classification	Percent
265-150-3	64742-48-9	-	Asp. Tox. 1: H304; Flam. Liq. 3: H226	30-50%

2-BUTANONE OXIME - REACH registered number(s): 01-2119539477-28-XXXX

202-496-6	96-29-7	-	Carc. 2: H351; Acute Tox. 4: H312; Eye Dam. 1: H318; Skin Sens. 1: H317	<1%
-----------	---------	---	---	-----

ZIRCONIUM BIS(2-ETHYLHEXANOATE) - REACH registered number(s): 01-2119979088-21

245-018-1	22464-99-9	-	Repr. 2: H361d	<1%
-----------	------------	---	----------------	-----

COBALT BIS(2-ETHYLHEXANOATE) - REACH registered number(s): 01-2119524678-29-XXXX

205-250-6	136-52-7	-	Skin Sens. 1: H317; Aquatic Acute 1: H400	<1%
-----------	----------	---	---	-----

## Section 4: First aid measures

### 4.1. Description of first aid measures

**Skin contact:** Wash immediately with plenty of soap and water. Remove all contaminated clothes and footwear immediately unless stuck to skin.

**Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.

**Ingestion:** Wash out mouth with water. Consult a doctor.

**Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

[cont...]

# SAFETY DATA SHEET

## FLOOR PAINT

Page: 3

### 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and pain.

**Ingestion:** There may be irritation of the throat.

**Inhalation:** There may be a feeling of tightness in the chest with shortness of breath.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

### 4.3. Indication of any immediate medical attention and special treatment needed

**Immediate / special treatment:** Show this safety data sheet to the doctor in attendance.

## Section 5: Fire-fighting measures

### 5.1. Extinguishing media

**Extinguishing media:** Alcohol resistant foam. Carbon dioxide. Dry chemical powder. Do not use water.

### 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** In combustion emits toxic fumes.

### 5.3. Advice for fire-fighters

**Advice for fire-fighters:** Wear self-contained breathing apparatus.

## Section 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions:** Refer to section 8 of SDS for personal protection details.

### 6.2. Environmental precautions

**Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding.

### 6.3. Methods and material for containment and cleaning up

**Clean-up procedures:** Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Refer to section 13 of SDS for suitable method of disposal.

### 6.4. Reference to other sections

**Reference to other sections:** Refer to section 13 of SDS.

## Section 7: Handling and storage

### 7.1. Precautions for safe handling

**Handling requirements:** Smoking is forbidden. Ensure there is sufficient ventilation of the area.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage conditions:** Store in a cool, well ventilated area. Keep away from sources of ignition.

**Suitable packaging:** Must only be kept in original packaging.

**Storage quantity limits:** 250 L

[cont...]

# SAFETY DATA SHEET

FLOOR PAINT

Page: 4

## 7.3. Specific end use(s)

**Specific end use(s):** PC9a: Coatings and paints, thinners, paint removers.

## Section 8: Exposure controls/personal protection

### 8.1. Control parameters

**Hazardous ingredients:**

**LOW BOILING POINT HYDROGEN TREATED NAPHTHA - NAPHTHA (PETROLEUM), HYDROTREATED HEAVY**

**Workplace exposure limits:**

**Respirable dust**

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	150 ppm	-	-	-

### DNEL/PNEC Values

**DNEL / PNEC** No data available.

### 8.2. Exposure controls

**Engineering measures:** Ensure there is sufficient ventilation of the area.

**Respiratory protection:** Respiratory protection not required.

**Hand protection:** Protective gloves.

**Eye protection:** Tightly fitting safety goggles.

**Skin protection:** Protective clothing.

**Environmental:** Prevent from entering in public sewers or the immediate environment.

## Section 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

**State:** Liquid

**Colour:** Various

**Odour:** Characteristic odour

**Evaporation rate:** Slow

**Oxidising:** Non-oxidising (by EC criteria)

**Solubility in water:** Insoluble

**Also soluble in:** Most organic solvents.

**Viscosity:** Non-viscous

**Boiling point/range°C:** 149 - 213

**Melting point/range°C:** N/A

**Flammability limits %: lower:** 0.6

**upper:** 6

**Flash point°C:** 43

**Part.coeff. n-octanol/water:** 5 - 6.7 (log Pow)

**Autoflammability°C:** 250

**Vapour pressure:** 300 Pa @20 deg C

**Relative density:** 1.21

**pH:** Not applicable.

**VOC g/l:** 435

[cont...]

# SAFETY DATA SHEET

FLOOR PAINT

Page: 5

## 9.2. Other information

**Other information:** Not applicable.

## Section 10: Stability and reactivity

### 10.1. Reactivity

**Reactivity:** Stable under recommended transport or storage conditions.

### 10.2. Chemical stability

**Chemical stability:** Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

**Hazardous reactions:** Hazardous reactions will not occur under normal transport or storage conditions.

### 10.4. Conditions to avoid

**Conditions to avoid:** Sources of ignition. Flames. Heat. Hot surfaces.

### 10.5. Incompatible materials

**Materials to avoid:** Strong acids. Strong bases. Strong oxidising agents.

### 10.6. Hazardous decomposition products

**Haz. decomp. products:** In combustion emits toxic fumes.

## Section 11: Toxicological information

### 11.1. Information on toxicological effects

**Hazardous ingredients:**

#### LOW BOILING POINT HYDROGEN TREATED NAPHTHA - NAPHTHA (PETROLEUM), HYDROTREATED HEAVY

DERMAL	RBT	LD50	>5000	mg/kg
ORAL	RAT	LD50	>5000	mg/kg
VAPOURS	RAT	4H LC50	>5000	mg/l

#### 2-BUTANONE OXIME

ORL	MUS	LD50	1	gm/kg
ORL	RAT	LD50	930	mg/kg
SCU	RAT	LD50	2702	mg/kg

**Relevant hazards for substance:**

Hazard	Route	Basis
Aspiration hazard	-	Hazardous: calculated

## Symptoms / routes of exposure

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and pain.

[cont...]

# SAFETY DATA SHEET

FLOOR PAINT

Page: 6

**Ingestion:** There may be irritation of the throat.

**Inhalation:** There may be a feeling of tightness in the chest with shortness of breath.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

**Other information:** Not applicable.

## Section 12: Ecological information

### 12.1. Toxicity

**Ecotoxicity values:** No data available.

### 12.2. Persistence and degradability

**Persistence and degradability:** No data available.

### 12.3. Bioaccumulative potential

**Bioaccumulative potential:** No data available.

### 12.4. Mobility in soil

**Mobility:** No data available.

### 12.5. Results of PBT and vPvB assessment

**PBT identification:** This product is not identified as a PBT/vPvB substance.

### 12.6. Other adverse effects

**Other adverse effects:** No data available.

## Section 13: Disposal considerations

### 13.1. Waste treatment methods

**Disposal operations:** Transfer to a suitable container and arrange for collection by specialised disposal company.

**Recovery operations:** Solvent reclamation/regeneration.

**Waste code number:** 08 01 11

**Disposal of packaging:** Retain for recovery.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

## Section 14: Transport information

### 14.1. UN number

**UN number:** UN1263

### 14.2. UN proper shipping name

**Shipping name:** PAINT

### 14.3. Transport hazard class(es)

**Transport class:** 3

[cont...]

# SAFETY DATA SHEET

FLOOR PAINT

Page: 7

## 14.4. Packing group

Packing group: III

## 14.5. Environmental hazards

Environmentally hazardous: No

Marine pollutant: No

## 14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D/E

Transport category: 3

## Section 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

### 15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

## Section 16: Other information

### Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

\* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: EUH208: Contains <name of sensitising substance>. May produce an allergic reaction.

H226: Flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

H312: Harmful in contact with skin.

H317: May cause an allergic skin reaction.

H318: Causes serious eye damage.

H351: Suspected of causing cancer <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

H361d: Suspected of damaging the unborn child.

H400: Very toxic to aquatic life.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.