
TYPE	Water borne stain base.
USE	All types of wood.
SPECIAL PROPERTIES	TEKNOSTAIN AQUA 1996-00 Base T, is based on acrylic binder.

TECHNICAL DATA

Density	Approx. 1.01 kg/l
Solid	Approx. 6 % by weight
Volatile organic compound (VOC)	See Safety Data Sheet.
Storage	Storage stability: See label.
System	To be used with TEKNOSTAIN AQUA 1996-10 Tinters.

INSTRUCTION FOR USE

Application method	Spraying, dipping and flow coat.	
Drying time	<u>20 °C</u> 1 hour.	<u>40 °C</u> 10 min.
Thinner	Water	
Cleaning	Water and TEKNOCLEAN 1954-00.	

HEALTH AND SAFETY	See Safety Data Sheet.
--------------------------	------------------------

The above information is normative and based on laboratory tests and practical experiences. The information is noncommittal, and we cannot accept liability for the results obtained under working conditions beyond our control, and consequently the buyer or the user is not released from the obligation to test the suitability of our products for specific means and application methods under the actual application conditions. Our liability covers only damage caused directly by defects in the products supplied by Teknos. The latest versions of Teknos' Technical Data Sheets and Safety Data Sheets are available from our homepage www.teknos.com.
