



## Safety Data Sheet

Copyright, 2012, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilising 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document group:</b>	30-5095-2	<b>Version number:</b>	1.00
<b>Revision date:</b>	23/01/2012	<b>Supersedes date:</b>	Initial issue.
<b>Transportation version number:</b>	4.00 (07/03/2012)		

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

3M Scotchkote Urethane Roof Coating SD 650 (Part B)

#### Product identification numbers

GR-2001-4026-1

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### Identified uses

Elastomeric roof coating

#### 1.3. Details of the supplier of the substance or mixture

**Address:** 3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.

**E Mail:** tox.uk@mmm.com

**Website:** www.3M.com/uk

#### 1.4. Emergency telephone number

+44 (0)1344 858 000

### SECTION 2: Hazard identification

#### 2.1. Classification of the substance or mixture

**Dangerous substances(67/548/EEC)/preparations(1999/45/EC) directive**

**Indication of danger**

Flammable

#### 2.2. Label elements

**Dangerous substances(67/548/EEC)/preparations(1999/45/EC) directive**

**Symbols** None.

**Contains:**

## 3M Scotchkote Urethane Roof Coating SD 650 (Part B)

No ingredients are assigned to the label.

### Risk phrases

R10 Flammable.

### Safety phrases

S16 Keep away from sources of ignition - No Smoking.  
S23C Do not breathe vapour or spray.  
S51 Use only in well ventilated areas.

### 2.3. Other hazards

None known.

## SECTION 3: Composition/information on ingredients

Ingredient	CAS Nbr	EU Inventory	% by Wt	Classification
Polyurethane	Trade Secret		85 - 95	
Xylene	1330-20-7	EINECS 215-535-7	1 - 10	Xn:R20-21; Xi:R38; R10 - Nota C (EU)  Flam. Liq. 3, H226; Acute Tox. 4, H332; Acute Tox. 4, H312; Skin Irrit. 2, H315 - Nota C (CLP)
Carbon black	1333-86-4	EINECS 215-609-9	< 1	
Ethylbenzene	100-41-4	EINECS 202-849-4	< 1	F:R11; Xn:R20 (EU)  Flam. Liq. 2, H225; Acute Tox. 4, H332 (CLP)

Please see section 16 for the full text of any R phrases and H statements referred to in this section

Please refer to section 15 for the any applicable Notas that have been applied to the above components

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### Eye contact

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

#### Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

#### Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

#### If swallowed

Rinse mouth. If you feel unwell, get medical attention.

**4.2. Most important symptoms and effects, both acute and delayed**

See Section 11.1 Information on toxicological effects

**4.3. Indication of any immediate medical attention and special treatment required**

Not applicable

**SECTION 5: Fire-fighting measures**

**5.1. Extinguishing media**

In case of fire: Use a fire fighting agent suitable for flammable liquids or gases such as dry chemical or carbon dioxide.

**5.2. Special hazards arising from the substance or mixture**

Closed containers exposed to heat from fire may build pressure and explode.

**5.3. Advice for fire-fighters**

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture.

**SECTION 6: Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Ventilate the area with fresh air. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Warning: A motor could be an ignition source and could cause flammable gases or vapours in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

**6.2. Environmental precautions**

Avoid release to the environment.

**6.3. Methods and material for containment and cleaning up**

Contain spill. Cover spill area with a fire-extinguishing foam. An appropriate aqueous film forming foam (AFFF) is recommended. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a toxic, corrosivity or flammability hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible.

**6.4. Reference to other sections**

Refer to Section 8 and Section 13 for more information

**SECTION 7: Handling and storage**

**7.1. Precautions for safe handling**

For industrial or professional use only. Do not handle until all safety precautions have been read and understood. Do not get in eyes, on skin, or on clothing. Do not breathe dust/fume/gas/mist/vapours/spray. Do not use in a confined area or areas with little or no air movement. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Take precautionary measures against static discharge. Wear low static or properly grounded shoes. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (eg. gloves, respirators...) as required. Do not eat, drink or smoke when using this product. Wash thoroughly after handling.

**7.2. Conditions for safe storage including any incompatibilities**

## 3M Scotchkote Urethane Roof Coating SD 650 (Part B)

Store away from acids. Store away from oxidising agents. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store away from strong bases.

### 7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational exposure limits

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Ethylbenzene	100-41-4	Health and Safety Comm. (UK)	TWA:441 mg/m <sup>3</sup> (100 ppm);STEL:552 mg/m <sup>3</sup> (125 ppm)	Skin Notation
Xylene	1330-20-7	Health and Safety Comm. (UK)	TWA:220 mg/m <sup>3</sup> (50 ppm);STEL:441 mg/m <sup>3</sup> (100 ppm)	Skin Notation
Carbon black	1333-86-4	Health and Safety Comm. (UK)	TWA: 3.5 mg/m <sup>3</sup> ; STEL: 7 mg/m <sup>3</sup>	

Health and Safety Comm. (UK) : UK Health and Safety Commission

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

ppm: parts per million

mg/m<sup>3</sup>: milligrams per cubic metre

CEIL: Ceiling

### 8.2. Exposure controls

#### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment. Use explosion-proof ventilation equipment.

#### 8.2.2. Personal protective equipment (PPE)

##### Eye/face protection

Wear eye/face protection.

The following eye protection(s) are recommended: Safety glasses with side shields.

##### Skin/hand protection

Gloves made from the following material(s) are recommended: Polymer laminate

The following protective clothing material(s) are recommended: Apron - polymer laminate

##### Respiratory protection

Select one of the following approved respirators based on airborne concentration of contaminants and in accordance with regulations:

Half facepiece or fullface air-purifying respirator with organic vapour cartridges and P2 particulate prefilters.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Specific Physical Form:	Viscous.
Appearance/Odour	Odourless; Yellowish colour.
pH	<i>Not applicable.</i>
Boiling point/boiling range	137 °C
Melting point	<i>Not applicable.</i>
Flammability (solid, gas)	Flammable liquid: Category 3.
Explosive properties	Not classified
Oxidising properties	Not classified
Flash point	25 °C [ <i>Test Method</i> :Closed Cup]
Autoignition temperature	375 °C
Flammable Limits(LEL)	1 % volume
Flammable Limits(UEL)	7 % volume
Vapour pressure	133.3 Pa [ <i>@ 21 °C</i> ]
Relative density	1.05 [ <i>Ref Std</i> :WATER=1]
Water solubility	Negligible
Partition coefficient: n-octanol/water	<i>No data available.</i>
Evaporation rate	<i>No data available.</i>
Vapour density	<i>No data available.</i>
Viscosity	<i>No data available.</i>
Density	1.04 g/ml

### 9.2. Other information

Volatile organic compounds (VOC)	100 g/l [ <i>Test Method</i> :Estimated] [ <i>Details</i> :EU Directive 2004/42/EC annex IIA (j) <500 g/l (from 1.1.2010)]
Percent volatile	6.08 % weight

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

### 10.2 Chemical stability

Stable.

### 10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

### 10.4 Conditions to avoid

None known.

### 10.5 Incompatible materials

Accelerators  
Alcohols.  
Amines.  
Strong acids.  
Strong bases.

## 3M Scotchkote Urethane Roof Coating SD 650 (Part B)

Strong oxidising agents.

Moisture.

### 10.6 Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
Carbon dioxide.	Not specified.
Carbon monoxide.	Not specified.

## SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

### 11.1 Information on Toxicological effects

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Eye contact

Vapours released during curing may cause eye irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

#### Skin contact

Contact with the skin during product use is not expected to result in significant irritation.

#### Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause target organ effects after inhalation.

#### Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

#### Target Organ Effects:

Auditory effects: Signs/symptoms may include hearing impairment, balance dysfunction and ringing in the ears.

Prolonged or repeated exposure may cause:

Neurological effects: Signs/symptoms may include personality changes, lack of coordination, sensory loss, tingling or numbness of the extremities, weakness, tremors, and changes in blood pressure and heart rate.

#### Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

### Toxicological Data

#### Acute Toxicity

Name	Route	Species	Value	UN GHS Classification
Overall product	Ingestion		No test data available; calculated ATE >5,000 mg/kg	Not classified (92% unknown)
Polyurethane			No data available	
Xylene	Dermal	Rabbit	LD50 > 4,300 mg/kg	Category5
Xylene	Inhalation-Vapor	Rat	LC50 28 mg/l	Category5

**3M Scotchkote Urethane Roof Coating SD 650 (Part B)**

	(4 hours)			
Xylene	Ingestion	Rat	LD50 3,523 mg/kg	Category5
Ethylbenzene	Dermal	Rabbit	LD50 15,433 mg/kg	Not classified
Ethylbenzene	Inhalation-Vapor (4 hours)	Rat	LC50 17 mg/l	Category4
Ethylbenzene	Ingestion	Rat	LD50 4,769 mg/kg	Category5
Carbon black	Dermal	Rabbit	LD50 > 3,000 mg/kg	Not classified
Carbon black	Ingestion	Rat	LD50 > 8,000 mg/kg	Not classified

ATE = acute toxicity estimate

**Skin Corrosion/Irritation**

Name	Species	Value	UN GHS Classification
Overall product		No test data available; calculated to cause no significant irritation	Not classified
Polyurethane		No data available	
Xylene		Mild irritant	Category 3
Ethylbenzene		Mild irritant	Category 3
Carbon black		No significant irritation	Not classified

**Serious Eye Damage/Irritation**

Name	Species	Value	UN GHS Classification
Overall product		No test data available; calculated to cause no significant irritation	Not classified
Polyurethane		No data available	
Xylene		Mild irritant	Not classified
Ethylbenzene		Moderate irritant	Category 2B
Carbon black		No data available	

**Skin Sensitisation**

Name	Species	Value	UN GHS Classification
Overall product		No test data available.	Not classified based on component data
Polyurethane		No data available	
Xylene		No data available	
Ethylbenzene		Not sensitizing	Not classified
Carbon black		No data available	

**Respiratory Sensitisation**

Name	Species	Value	UN GHS Classification
Overall product		No test data available.	Not classified based on component data
Polyurethane		No data available	
Xylene		No data available	
Ethylbenzene		No data available	
Carbon black		No data available	

**Germ Cell Mutagenicity**

Name	Route	Value	UN GHS Classification
Overall product		No data available	Overall Germ Cell Mutagenicity classification Not classified
Overall product		No test data available.	
Polyurethane		No data available	
Xylene	In Vitro	Not mutagenic	Not classified
Xylene	In vivo	Not mutagenic	Not classified
Ethylbenzene	In Vitro	Some positive data exist, but the data are not sufficient for classification	Not classified

**3M Scotchkote Urethane Roof Coating SD 650 (Part B)**

Carbon black	In vivo	Some positive data exist, but the data are not sufficient for classification	Not classified
--------------	---------	--	----------------

**Carcinogenicity**

Name	Route	Species	Value	UN GHS Classification
Overall product			No test data available.	Category 2 based on component data
Polyurethane			No data available	
Xylene	Dermal		Not carcinogenic	Not classified
Xylene	Ingestion		Not carcinogenic	Not classified
Xylene	Inhalation		Some positive data exist, but the data are not sufficient for classification	Not classified
Ethylbenzene	Inhalation		Carcinogenic.	Category 2
Carbon black	Dermal		Not carcinogenic	Not classified
Carbon black	Ingestion		Not carcinogenic	Not classified
Carbon black	Inhalation		Carcinogenic.	Category 2

**Reproductive Toxicity****Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration	UN GHS Classification
Overall product		No test data available.				Not classified based on component data
Polyurethane		No data available				
Xylene	Ingestion	Some positive reproductive/developmental data exist, but the data are not sufficient for classification		LOAEL 2,060 mg/kg/day		
Xylene	Inhalation	Some positive reproductive/developmental data exist, but the data are not sufficient for classification		NOAEL N/A		
Ethylbenzene	Inhalation	Some positive reproductive/developmental data exist, but the data are not sufficient for classification		LOEL 0.43 mg/l		
Carbon black		No data available				

**Lactation**

Name	Route	Species	Value	UN GHS Classification
Overall product			No test data available.	Not classified based on component data
Xylene	Ingestion		Does not cause effects on or via lactation	Not classified

**Target Organ(s)**



**3M Scotchkote Urethane Roof Coating SD 650 (Part B)**

**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration	UN GHS Classification
Overall product			No test data available.				Category 1 based on component data
Polyurethane			No data available				
Xylene	Inhalation	auditory system	Causes damage to organs		LOAEL 6.3 mg/l		Category 1
Xylene	Inhalation	central nervous system depression	May cause drowsiness or dizziness		LOAEL 0.43 mg/l		Category 3
Xylene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		Irritation Positive		Not classified
Xylene	Inhalation	liver	Some positive data exist, but the data are not sufficient for classification		NOEL N/A		Not classified
Xylene	Inhalation	eyes	Some positive data exist, but the data are not sufficient for classification		NOEL 3.5 mg/l		Not classified
Xylene	Inhalation	nervous system	All data are negative		NOAEL 0.65 mg/l		Not classified
Xylene	Ingestion	central nervous system depression	May cause drowsiness or dizziness		NOAEL N/A		Category 3
Xylene	Ingestion	eyes	Some positive data exist, but the data are not sufficient for classification		NOEL 125 mg/kg		Not classified
Ethylbenzene	Inhalation	central nervous system depression	May cause drowsiness or dizziness		LOAEL 0.43 mg/l		Category 3
Ethylbenzene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		Irritation Positive		Not classified
Carbon black	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		Irritation Positive		Not classified

**Specific Target Organ Toxicity - repeated exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration	UN GHS Classification
Overall product			No test data available.				Category 1 based on component data

**3M Scotchkote Urethane Roof Coating SD 650 (Part B)**

Polyurethane			No data available				
Xylene	Inhalation	nervous system	Causes damage to organs through prolonged or repeated exposure		LOAEL 0.4 mg/l		Category 1
Xylene	Inhalation	auditory system	May cause damage to organs through prolonged or repeated exposure		LOAEL 7.8 mg/l		Category 2
Xylene	Inhalation	liver	Some positive data exist, but the data are not sufficient for classification		NOEL N/A		Not classified
Xylene	Inhalation	heart   endocrine system   hematopoietic system   muscles   kidney and/or bladder   respiratory system	All data are negative		NOAEL 3.5 mg/l		Not classified
Xylene	Ingestion	auditory system	Some positive data exist, but the data are not sufficient for classification		LOEL 900 mg/kg/day		Not classified
Xylene	Ingestion	liver   kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification		NOEL N/A		Not classified
Xylene	Ingestion	heart   skin   endocrine system   bone, teeth, nails, and/or hair   hematopoietic system   immune system   nervous system   respiratory system	All data are negative		NOAEL 1,000 mg/kg/day		Not classified
Ethylbenzene	Inhalation	liver   kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification		NOAEL 1.1 mg/l		Not classified
Ethylbenzene	Inhalation	auditory system	Some positive data exist, but the data are not sufficient for classification		NOEL 1.3 mg/l		Not classified
Ethylbenzene	Inhalation	endocrine system	Some positive data exist, but the data are not sufficient for classification		NOEL 0.32 mg/l		Not classified
Ethylbenzene	Inhalation	hematopoietic system	Some positive data exist, but the data are not sufficient		NOEL 1.6 mg/l		Not classified

**3M Scotchkote Urethane Roof Coating SD 650 (Part B)**

			for classification			
Ethylbenzene	Inhalation	heart	All data are negative		NOAEL 3.2 mg/l	Not classified
Ethylbenzene	Inhalation	bone, teeth, nails, and/or hair	All data are negative		NOAEL 4.2 mg/l	Not classified
Ethylbenzene	Inhalation	immune system	All data are negative		NOAEL 3.2 mg/l	Not classified
Ethylbenzene	Inhalation	muscles	All data are negative		NOAEL 4.2 mg/l	Not classified
Ethylbenzene	Inhalation	respiratory system	All data are negative		NOAEL 3.2 mg/l	Not classified
Ethylbenzene	Ingestion	liver	Some positive data exist, but the data are not sufficient for classification		NOEL 136 mg/kg/day	Not classified
Ethylbenzene	Ingestion	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification		NOEL 136 mg/kg	Not classified
Carbon black	Inhalation	heart	Some positive data exist, but the data are not sufficient for classification		NOEL N/A	Not classified
Carbon black	Inhalation	pneumoconiosis	Some positive data exist, but the data are not sufficient for classification		NOAEL N/A	Not classified

**Aspiration Hazard**

Name	Value	UN GHS Classification
Overall product	No test data available.	Not classified based on component and/or viscosity data
Polyurethane	Not an aspiration hazard	Not classified
Xylene	Aspiration hazard	Category 1
Ethylbenzene	Aspiration hazard	Category 1
Carbon black	Not an aspiration hazard	Not classified

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

**SECTION 12: Ecological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

**12.1. Toxicity****Acute aquatic hazard:**

Not acutely toxic to aquatic life by GHS criteria.

**Chronic aquatic hazard:**

Not chronically toxic to aquatic life by GHS criteria.

## 3M Scotchkote Urethane Roof Coating SD 650 (Part B)

No product test data available.  
No component test data available.

### 12.2. Persistence and degradability

No test data available.

### 12.3 : Bioaccumulative potential

No test data available.

### 12.4. Mobility in soil

Please contact manufacturer for more details

### 12.5. Results of the PBT and vPvB assessment

No information available at this time, contact manufacturer for more details

### 12.6. Other adverse effects

No information available.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations

Incinerate in a permitted waste incineration facility. Dispose of waste product in a permitted industrial waste facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

### EU waste code (product as sold)

08 01 11\* Waste paint and varnish containing organic solvents or other dangerous substances

## SECTION 14: Transportation information

GR-2001-4026-1

**ADR/RID:** UN1263, PAINT RELATED MATERIAL, LIMITED QUANTITY, 3., III, (--), ADR Classification Code: F1.

**IMDG-CODE:** UN1263, PAINT RELATED MATERIAL, 3, III, LIMITED QUANTITY, EMS: FE,SE.

**ICAO/IATA:** UN1263, PAINT RELATED MATERIAL, 3., III.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Carcinogenicity

**Ingredient**  
Carbon black

**CAS Nbr**  
1333-86-4

**Classification**  
Grp. 2B: Possible human

**Regulation**  
International Agency

### 3M Scotchkote Urethane Roof Coating SD 650 (Part B)

Ethylbenzene	100-41-4	carc. Grp. 2B: Possible human	for Research on Cancer International Agency
Xylene	1330-20-7	carc. Gr. 3: Not classifiable	for Research on Cancer International Agency for Research on Cancer

#### Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korean Toxic Chemical Control Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. The components of this product are in compliance with the chemical notification requirements of TSCA.

#### 15.2. Chemical Safety Assessment

Not applicable

## SECTION 16: Other information

#### List of relevant H statements

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H332	Harmful if inhaled.

#### List of relevant R-phrases

R10	Flammable.
R11	Highly flammable.
R20	Harmful by inhalation.
R21	Harmful in contact with skin.
R38	Irritating to skin.

#### Revision information:

No revision information is available.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

3M United Kingdom MSDSs are available at [www.3M.com/uk](http://www.3M.com/uk)