

Centrecoat™

Premium Chlorinated Rubber Line Marking



Technical Data Sheet

PRODUCT DESCRIPTION

A quick drying line marking paint for use on bare concrete or asphalt, Centrecoat Premium Chlorinated Rubber Line Marking may also be used on aged blacktop, thermoplastic coverings, and most types of painted lines and floor paints. Suitable for roads, car parks and factory lines.

PROPERTIES

Fast drying
Suitable for interior & exterior
Meets BS6044
Can be hand sprinkled with glass beads
High build
Good chemical resistance

RECOMMENDED APPLICATION METHODS

Brush or roller for small areas. Line Lazer type machines for large areas.
Surfaces must be clean, dry and free from oil and grease contamination, loose dust or laitance.
Acid etch concrete if in doubt to remove heavy laitance, or preferably shot blast.
Asphalt and other similar surfaces should be allowed to through harden for up to 6 months.
Minimum application temperature: 8°C.

TECHNICAL

Appearance:	Liquid
Colour:	White
Odour:	Characteristic Aromatic Hydrocarbons
Solubility:	Slightly soluble in water
Relative Density:	1.5
Vapour Density (air=1):	Heavier than air
Thinner:	Toluene

COVERAGE

Theoretical: 2.85m² per litre; approximately 50-57 metres of line at 5cm.

AVERAGE DRYING TIMES

In still air conditions the following times can be achieved with a relative humidity of 60% at 20°C.

Touch Dry: 10 to 15 minutes.
Full cure: 4 hours.

PACKAGING

Supplied in 5 and 20 litre containers.
Shelf life: 6 months.
Store between: 5 and 35°C.