

PRODUCT DATA

ELASTOFILL

DESCRIPTION

Elastic jointing paste based on acrylic dispersions.

MAIN PROPERTIES

Forms a rubberlike mass with permanently high elasticity (> 900%) after evaporation of the water - can absorb strong expansions and deformations - alkali resistant - very resistant to ageing, weather and temperature variations - waterproof - very good adhesion - easy application.

RECOMMENDED USES

Sealing, jointing, filling, fixing, glueing on concrete, wood, metal, glass, hard PVC, tiles, plaster, alu-bitumen, etc.

TECHNICAL DATA

Appearance:	Satin gloss (gloss 60°: ± 15%)
Colour:	White - grey - black - brown - beige - transparent
Density:	± 1,3 g/cm ³
Solids Content:	In volume: 64 - 67% In weight: 72 - 75%
Recommended film thickness:	Wet film: Max. 10 mm Dry film: Max. 6,5 mm
VOC-content:	Max. 5 g/l
Flashpoint:	Not flammable
Drying times	20°C/50% r.h.
To touch:	3 hours, film thickness 8 mm
To handle:	8 hours, film thickness 8 mm
To recoat:	1 day, film thickness 8 mm
Full hardness	± 1 week, film thickness 8 mm

Coverage

Theoretical per cartridge: For a joint of 10 mm wide and 15 mm deep: ± 6 metres run.
Jointing paste has to be applied in max. 10 mm wet film thickness.

SURFACE PREPARATION

Grind out fine cracks in V-shape till about 0,5 cm wide; if depth > 1/2 x width, apply a back filling. The crack edges must be primed with Parafix, Pegafix or Vernac (diluted with Thinner 22). Hard PVC is to be primed with Primer 44 HS, metal and glass with diluted Noxyde.

APPLICATION & THINNING

Tools: Manual spray gun (nozzle free to choose) - spatula, palette knife, glue spreader (combed lime rills ± 3 mm thick).

Cleanup: Water. After drying Elastofill can only be removed mechanically or softened with a synthetic thinner; then remove by rubbing or scratching.

Remarks: Joints have to be smoothed with a finger or with a cloth soaked in Thinner 22 or in water (+ soap).
The surface in contact with the air must be sufficiently large, since Elastofill is to be transformed into a rubber like mass by evaporation of the water.
On porous surfaces, always use an appropriate primer.

Rust-Oleum Netherlands B.V.

Braak 1, 4704 RJ
P.O. Box 138, 4700 AC
Roosendaal, The Netherlands
T +31 (0)165 593 636
F +31 (0)165 593 600
info.nl@ro-m.com
www.ro-m.com

N.V. Martin Mathys S.A.

Kolenbergstraat 23
B - 3545 Zelem
Halen, Belgium
T +32 (0)13 460 200
F +32 (0)13 460 201
info.be@ro-m.com
www.ro-m.com

Rust-Oleum France S.A.S

11, Rue Jules Verne, B.P. 60039
95322 St-Leu-la-Forêt Cedex
France
T +33 (0)130 400 044
F +33 (0)130 409 980
info.fr@ro-m.com
www.ro-m.com

Rust-Oleum UK Ltd.

Unit 6, Spitfire Close
Coventry Business Park
Coventry, CV5 6UR
United Kingdom
T +44 (0)2476 717 329
F +44 (0)2476 718 930
info.uk@ro-m.com
www.ro-m.com

Rust-Oleum Mathys Italia s.r.l.

Largo Donegani 2
20121 Milano, Italia
T +39 335 10 93 482
info.it@ro-m.com
www.ro-m.com

PRODUCT DATA

ELASTOFILL

APPLICATION CONDITIONS

Minimum temperature: 5°C / Max. Relative humidity: 80%.

REMARKS

Elastofill can be recoated with the following paints : acrylic paints Murfill, Paracem (Elastofill has to be isolated first with Porisol), Paracem Semi-Gloss, Pegacryl, Pegacryl Satin for inside and outside works, Pegaflo for inside works; with high and satin gloss alkyd enamels; with Porisol and Pegatex.

SAFETY

Consult Safety Data Sheet and Safety Information printed on the can.

SHELLIFE / STORAGE CONDITIONS

2 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5° and 35°C.

Rust-Oleum Netherlands B.V.

Braak 1, 4704 RJ
P.O. Box 138, 4700 AC
Roosendaal, The Netherlands
T +31 (0)165 593 636
F +31 (0)165 593 600
info.nl@ro-m.com
www.ro-m.com

N.V. Martin Mathys S.A.

Kolenbergstraat 23
B - 3545 Zelem
Halen, Belgium
T +32 (0)13 460 200
F +32 (0)13 460 201
info.be@ro-m.com
www.ro-m.com

Rust-Oleum France S.A.S

11, Rue Jules Verne, B.P. 60039
95322 St-Leu-la-Forêt Cedex
France
T +33 (0)130 400 044
F +33 (0)130 409 980
info.fr@ro-m.com
www.ro-m.com

Rust-Oleum UK Ltd.

Unit 6, Spitfire Close
Coventry Business Park
Coventry, CV5 6UR
United Kingdom
T +44 (0)2476 717 329
F +44 (0)2476 718 930
info.uk@ro-m.com
www.ro-m.com

Rust-Oleum Mathys Italia s.r.l.

Largo Donegani 2
20121 Milano, Italia
T +39 335 10 93 482
info.it@ro-m.com
www.ro-m.com