



SAFETY DATA SHEET

Anglo Epoxy Floor Paint Resin

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING

PRODUCT NAME Anglo Epoxy Floor Paint Resin

SUPPLIER Anglo Building Products Ltd
 RUST-OLEUM UK Ltd
 Unit 6, Spitfire Close
 Coventry Business Park
 Coventry
 CV5 6UR
 +44 (0) 2476 717 329
 +44 (0) 2476 718 930
 info.uk@ro-m.com

2 HAZARDS IDENTIFICATION

Irritating to eyes and skin. May cause sensitisation by skin contact. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

CLASSIFICATION Xi;R36/38. R43. N;R51/53.

3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
EPOXY RESIN (Number average MW <= 700)	500-033-5	25068-38-6	60-100%	R43 Xi;R36/38 N;R51/53
Hexanediglycidyl ether	240-260-4	16096-31-4	10-30%	Xi;R36/38. R43,R52/53.

The Full Text for all R-Phrases are Displayed in Section 16

4 FIRST-AID MEASURES

INHALATION

Move the exposed person to fresh air at once. Rinse nose and mouth with water. Get medical attention if any discomfort continues.

INGESTION

NEVER MAKE AN UNCONSCIOUS PERSON VOMIT OR DRINK FLUIDS! Rinse mouth thoroughly. Get medical attention if any discomfort continues.

SKIN CONTACT

Remove affected person from source of contamination. Remove contaminated clothing. Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.

EYE CONTACT

Remove victim immediately from source of exposure. Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes and get medical attention.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

This product is not flammable. Use fire-extinguishing media appropriate for surrounding materials.

6 ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS

Wear protective clothing as described in Section 8 of this safety data sheet.

SPILL CLEAN UP METHODS

Stop leak if possible without risk. Absorb in vermiculite, dry sand or earth and place into containers. Flush with plenty of water to clean spillage area. Do not contaminate water sources or sewer.

7 HANDLING AND STORAGE

USAGE PRECAUTIONS

Avoid spilling, skin and eye contact.

Anglo Epoxy Floor Paint Resin

STORAGE PRECAUTIONS

Store in tightly closed original container in a dry, cool and well-ventilated place. Keep in original container.

STORAGE CLASS

Chemical storage.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

PROTECTIVE EQUIPMENT



PROCESS CONDITIONS

Provide eyewash station.

ENGINEERING MEASURES

Provide adequate ventilation. Observe Workplace Exposure Limits and minimise the risk of inhalation of vapours.

RESPIRATORY EQUIPMENT

No specific recommendation made, but respiratory protection may still be required under exceptional circumstances when excessive air contamination exists.

HAND PROTECTION

Use suitable protective gloves if risk of skin contact.

EYE PROTECTION

If risk of splashing, wear safety goggles or face shield.

OTHER PROTECTION

Wear appropriate clothing to prevent any possibility of skin contact.

HYGIENE MEASURES

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Liquid		
COLOUR	Amber		
ODOUR	No characteristic odour.		
SOLUBILITY	Insoluble in water		
RELATIVE DENSITY	>1.0	VOLATILE ORGANIC COMPOUND (VOC)	nil

10 STABILITY AND REACTIVITY

STABILITY

Stable under normal temperature conditions.

CONDITIONS TO AVOID

Avoid excessive heat for prolonged periods of time.

HAZARDOUS DECOMPOSITION PRODUCTS

Fire creates: Carbon monoxide (CO). Carbon dioxide (CO₂).

11 TOXICOLOGICAL INFORMATION

INHALATION

Irritating to respiratory system.

INGESTION

May cause stomach pain or vomiting.

SKIN CONTACT

May cause sensitisation by skin contact. Irritating to skin.

EYE CONTACT

Irritating to eyes.

Anglo Epoxy Floor Paint Resin

12 ECOLOGICAL INFORMATION

ECOTOXICITY

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

13 DISPOSAL CONSIDERATIONS

DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements.

14 TRANSPORT INFORMATION



UK ROAD CLASS	9		
PROPER SHIPPING NAME	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN (Number average MW ≤ 700))		
UN NO. ROAD	3082	UK ROAD PACK GR.	III
ADR CLASS NO.	9	ADR CLASS	Class 9: Miscellaneous dangerous substances and articles.
ADR PACK GROUP	III	HAZARD No. (ADR)	90
ADR LABEL NO.	9	HAZCHEM CODE	3Z
CEPIC TEC(R) NO.	90GM6-III	RID CLASS NO.	9
RID PACK GROUP	III	UN NO. SEA	3082
IMDG CLASS	9	IMDG PACK GR.	III
EMS	F-A, S-F	MFAG	See Guide
MARINE POLLUTANT		UN NO. AIR	3082



AIR CLASS	9	AIR PACK GR.	III
-----------	---	--------------	-----

15 REGULATORY INFORMATION

LABELLING



Irritant



Dangerous for the environment

CONTAINS	EPOXY RESIN (Number average MW ≤ 700) Hexanediglycidyl ether
----------	--

RISK PHRASES

R36/38	Irritating to eyes and skin.
R43	May cause sensitisation by skin contact.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

SAFETY PHRASES

S24/25	Avoid contact with skin and eyes.
S26	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

Anglo Epoxy Floor Paint Resin

S37	Wear suitable gloves.
S57	Use appropriate containment to avoid environmental contamination.
S60	This material and its container must be disposed of as hazardous waste.
S61	Avoid release to the environment. Refer to special instructions/safety data sheets.
P5	Contains epoxy constituents. See information supplied by the manufacturer.

STATUTORY INSTRUMENTS

Chemicals (Hazard Information and Packaging) Regulations.

APPROVED CODE OF PRACTICE

Safety Data Sheets for Substances and Preparations. Classification and Labelling of Substances and Preparations Dangerous for Supply.

GUIDANCE NOTES

Workplace Exposure Limits EH40. CHIP for everyone HSG(108).

16 OTHER INFORMATION

REVISION DATE 09/06/2006

REV. NO./REPL. SDS GENERATED 1

RISK PHRASES IN FULL

R36/38	Irritating to eyes and skin.
R43	May cause sensitisation by skin contact.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R52/53	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.



SAFETY DATA SHEET

Anglo Epoxy Floor Paint Curing Agent

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING

PRODUCT NAME Anglo Epoxy Floor Paint Curing Agent

SUPPLIER Anglo Building Products Ltd
 RUST-OLEUM UK Ltd
 Unit 6, Spitfire Close
 Coventry Business Park
 Coventry
 CV5 6UR
 +44 (0) 2476 717 329
 +44 (0) 2476 718 930
 info.uk@ro-m.com

2 HAZARDS IDENTIFICATION

Risk of serious damage to eyes.

CLASSIFICATION Xi;R41.

3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
2-BUTOXYETHANOL	203-905-0	111-76-2	< 1%	Xn;R20/21/22 Xi;R36/38
Polyamine - Epoxy resin adduct			10-30%	Xn;R22. Xi;R41.

The Full Text for all R-Phrases are Displayed in Section 16

4 FIRST-AID MEASURES

INHALATION

Move the exposed person to fresh air at once. Rinse nose and mouth with water. Get medical attention if any discomfort continues.

INGESTION

NEVER MAKE AN UNCONSCIOUS PERSON VOMIT OR DRINK FLUIDS! Rinse mouth thoroughly. Get medical attention if any discomfort continues.

SKIN CONTACT

Remove affected person from source of contamination. Remove contaminated clothing. Wash the skin immediately with soap and water. Get medical attention if irritation persists after washing.

EYE CONTACT

Remove victim immediately from source of exposure. Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Get medical attention immediately. Continue to rinse.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

This product is not flammable. Use fire-extinguishing media appropriate for surrounding materials.

6 ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS

Wear protective clothing as described in Section 8 of this safety data sheet.

SPILL CLEAN UP METHODS

Stop leak if possible without risk. Absorb in vermiculite, dry sand or earth and place into containers. Flush with plenty of water to clean spillage area. Do not contaminate water sources or sewer.

7 HANDLING AND STORAGE

USAGE PRECAUTIONS

Avoid spilling, skin and eye contact.

Anglo Epoxy Floor Paint Curing Agent

STORAGE PRECAUTIONS

Store in tightly closed original container in a dry, cool and well-ventilated place. Keep in original container.

STORAGE CLASS

Chemical storage.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	Std	LT - ppm	LT - mg/m3	ST - ppm	ST - mg/m3
2-BUTOXYETHANOL	OES	25 ppm(Sk)		50 ppm(Sk)	

PROTECTIVE EQUIPMENT



PROCESS CONDITIONS

Provide eyewash station.

ENGINEERING MEASURES

Provide adequate ventilation. Observe Workplace Exposure Limits and minimise the risk of inhalation of vapours.

RESPIRATORY EQUIPMENT

No specific recommendation made, but respiratory protection may still be required under exceptional circumstances when excessive air contamination exists.

HAND PROTECTION

Use suitable protective gloves if risk of skin contact.

EYE PROTECTION

If risk of splashing, wear safety goggles or face shield.

OTHER PROTECTION

Wear appropriate clothing to prevent any possibility of skin contact.

HYGIENE MEASURES

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Liquid	
COLOUR	Various	
ODOUR	Slight odour	
SOLUBILITY	Soluble in water	
RELATIVE DENSITY	>1.0	
		VOLATILE ORGANIC COMPOUND nil (VOC)

10 STABILITY AND REACTIVITY

STABILITY

Stable under normal temperature conditions.

CONDITIONS TO AVOID

Avoid excessive heat for prolonged periods of time.

HAZARDOUS DECOMPOSITION PRODUCTS

Fire creates: Carbon monoxide (CO). Carbon dioxide (CO₂).

11 TOXICOLOGICAL INFORMATION

INHALATION

Irritating to respiratory system.

INGESTION

May cause discomfort if swallowed.

SKIN CONTACT

Liquid may irritate skin.

Anglo Epoxy Floor Paint Curing Agent**EYE CONTACT**

Risk of serious damage to eyes.

12 ECOLOGICAL INFORMATION**ECOTOXICITY**

Not regarded as dangerous for the environment.

13 DISPOSAL CONSIDERATIONS**DISPOSAL METHODS**

Dispose of waste and residues in accordance with local authority requirements.

14 TRANSPORT INFORMATION

ROAD TRANSPORT NOTES	Not Classified
RAIL TRANSPORT NOTES	Not Classified.
SEA TRANSPORT NOTES	Not Classified.
AIR TRANSPORT NOTES	Not Classified.

15 REGULATORY INFORMATION**LABELLING**

Irritant

RISK PHRASES

R41	Risk of serious damage to eyes.
-----	---------------------------------

SAFETY PHRASES

S25	Avoid contact with eyes.
S26	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S39	Wear eye/face protection.
S60	This material and its container must be disposed of as hazardous waste.

STATUTORY INSTRUMENTS

Chemicals (Hazard Information and Packaging) Regulations.

APPROVED CODE OF PRACTICE

Safety Data Sheets for Substances and Preparations. Classification and Labelling of Substances and Preparations Dangerous for Supply.

GUIDANCE NOTES

Workplace Exposure Limits EH40. CHIP for everyone HSG(108).

16 OTHER INFORMATION

REVISION DATE 09/06/2006

REV. NO./REPL. SDS GENERATED 1

RISK PHRASES IN FULL

R20/21/22	Harmful by inhalation, in contact with skin and if swallowed.
R22	Harmful if swallowed.
R36/38	Irritating to eyes and skin.
R41	Risk of serious damage to eyes.