



FLOETROL



Water-based Paint Conditioner



- **Coverage:** N/A
- **Drying Time:** Paint Manufacturers Guidelines
- **Sizes:** 1ltr, 2.5ltr
- **Application:** Brush, Roller, Spray

Tip

When using a cup gun, if paint appears to thicken add up to one tablespoon of water to thin the paint
Do not add to clear acrylic varnishes



Water-based paints just flow
No Spatter, No Mess

Added Flow for Perfect Finishes

Floetrol is an additive specially formulated for use with all water-based paints, to help improve the finish, performance and ease application for the professional painter and decorator.

Unlike water, Floetrol does not weaken the paint but instead maintains its inherent qualities, characteristics and body. Extends the wet edge time to eliminate brush and roller marks, while improving its application properties, even in the most difficult painting conditions. Floetrol makes any water-based paint, work and feel like an oil-based paint.

Ideal for spraying Floetrol allows up to a 20% reduction in pressure without affecting the spray pattern. When spraying, Floetrol lubricates the paint, thus reducing wear and tear on the spray equipment as well as cutting down time from tip clogging in Airless and Cup guns, as well as piston freeze up in Cup guns.

For special effects, Floetrol gives you the time to create the look you want, by increasing the open time.

Floetrol may be used in any water-based paint whether it is emulsion, acrylic gloss or eggshell and woodstains

Eases Application

Reduces Brush & Roller Marks

A Must for Spray Painting

Improves Covering Power

Ideal for Special Effects

Saves Time & Money