

BLACKFRIAR PAINTS LTD

TECHNICAL DATA SHEET

BF0520003 Blackfriar Heat Resistant Black Paint.

Revision
date:
16/03/10

<u>Product Information</u>	<u>Technical Spec</u>	<u>Recommended Spreading Rate</u>
<p><u>Description</u></p> <p>A heat resistant hardwearing black satin finish for metal and wood.</p>	<p><u>Composition</u></p> <p>Based on a blend of long oil and urethane modified alkyd resins in low aromatic white spirits.</p>	<p>13m²/l</p>
<p><u>Usage/purpose</u></p> <p>For grates, fireside ornaments, radiators, barbecue exteriors etc.</p>	<p><u>VOC</u></p> <p>EU limit value for this product (cat A/i): 500 g/l (2010). This product contains max 500 g/l VOC</p>	<p><u>Thinning</u></p> <p>Up to 10% with white spirit</p>
<p><u>Characteristics</u></p> <p>A smooth finish that is heat resistant (up to) durable and protective.</p>	<p><u>Performance</u></p> <p>An attractive black paint ideal for use inside or outside. Heat resistant up to 200°C/400°F</p>	<p><u>Drying Time</u></p> <p>Touch dry in 2-4 hours Recoatable after 16 hours under normal conditions (20°C 50% RH).</p>
<p><u>Finish</u></p> <p>Satin Finish</p>	<p><u>Surface Preparation</u></p> <p>Ensure substrate to be painted is sound, clean and free from any rust, dirt, grease or any surface contaminants. Where necessary prime new and bare areas with the appropriate Blackfriar Primer.</p>	<p><u>Cleaning</u></p> <p>Clean application equipment or spills with white spirit or Blackfriar Brush Cleaner</p>
<p><u>Colour(s)</u></p> <p>Black</p>	<p><u>Application Method</u></p> <p>Brush, Roller, Spray Ensure products are thoroughly stirred with a broad stirrer prior to use. Apply at least two full coats.</p>	<p><u>Limitations</u></p> <p><u>NB.</u> Not for use on wood burning stoves or objects which come into direct contact with flames.</p>
<p><u>Packaging</u></p> <p>125ml, 250ml, 500ml, 1litre, 2.5litre. Larger sizes may be available on request dependent on volume required.</p>		<p><u>Environmental Info.</u></p> <p>Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Flammable</p>
<p><u>Disclaimer;</u></p> <p>The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. It is our recommendation that a trial area is first coated to ensure the product is satisfactory to individual requirements</p>	<p>For Technical Enquiries, Material Safety Data Sheets Telephone Sales on 0191 4106611</p>	<p>Paint Product UN No. 1263.</p>
		<p>Tor Coatings Ltd. Portobello Industrial Est, Birtley Chester-le Street County Durham DH3 2RE</p>