





Ultimate[™] Professional Exterior Wood Stain

The most technically advanced exterior wood stain in its class

Ultimate[™], as its name suggests, delivers the definitive durable finish without compromising looks or the environment, which is why it is proving a popular choice with architects and specifiers requiring a high performing product.

Formulated for durability, this technically superb exterior wood stain boasts a maintenance cycle of 12 years, while ensuring the same integrity and lustre throughout its long life.

Its advanced waterbourne system and exceptionally low Volatile Organic Compound (VOC) rating – the lowest of any stain available on the market today – means the impact on the environment is minimal, both immediate and over the long term. The ultra low VOC rating also makes Ultimate one of the safest stains available; air quality is preserved and incidents of eye and respiratory irritation, caused by exposure to fumes, is virtually non-existent.

Architects will appreciate the versatile colour palette, incorporating both traditional and contemporary hues and offering inspirational and dynamic colour choices. From subtle tones to bright and bold contemporary colours, the palette offers the ultimate in creative freedom.

Tough, durable and beautiful, Ultimate™ is a natural choice for architects or anyone who wants lasting performance without compromise.





Exterior Joinery – new woodwork, pressure impregnated timber and previously painted woodwork.

Drying Times at +23 °C

Touch dry: 2h

Recoatable: 8h, but dependent on temperature and humidity this can be less

Coverage

Sawn timber: 7-10m²/litre Planed timber: 10-12m²/litre

Maintenance Cycle

Up to 12 years provided application is in accordance with our guidance.

Application method

Brush, roller or airless spray.

Sizes

11, 31 and 101 cans



Ultimate[™] Windows and Doors

The most environmentally friendly exterior wood stain in its class

Demidekk Ultimate Windows and Doors is a waterborne exterior wood protection coating with very good colour stability and long maintenance cycles. Especially suited for smooth woodwork such as windows, doors, window frames, guttering, and other outdoor details.

The product contains film preserving agents, which combat surface fungi buildup on the substrate. Use as a system together with Visir Primer products.

Easy to apply with a long-lasting colour and shine. Good adhesive properties. Demidekk Ultimate Windows and Doors may be used on new woodwork and previously painted and stained woods as well as pressure impregnated wood. The product may also be used as a topcoat for plastic and metal objects if used with a suitable primer.



Exterior Joinery – new woodwork, pressure impregnated timber and previously painted woodwork.

Drying Times at +23 °C

Touch dry: 2h Recoatable: 4h

Coverage

Sawn timber: 6-9m2/litre Planed timber: 10-12m2/litre

Maintenance Cycle

Up to 12 years provided application is in accordance with our guidance.

Application method

Brush, roller or airless spray.

Sizes

1I and 3I cans



