

KEIM Universal Render Fine (Keim Universalputz Fein)



1. Product description

Keim Universal Render Fine is a renovation and thin layer exterior wall render, based on lime and silicates with a small amount of organic additives and fibre reinforcement, for use on all mineral substrates, both exterior and interior.

2. Field of application

Renovation and repair of sound existing renders, sound existing paint coats and for filling of cracks. Suitable for interior and exterior use.

Keim Universal Render Fine can be used as a base coat for subsequent decoration using Keim Mineral Paints.

3. Product properties

Binder based on pozzolan with calcite aggregates, light aggregates and fibre reinforcement, water repellent.

Grain size: 0 - 0.6mm
Bulk density: 1.2g/cm³

Material characteristics

Water absorption co-efficient:
 $w < 0.5 \text{ kg/m}^2 \cdot \text{h}^{0.5}$

Diffusion resistance value:
 $\mu = 8$

Comprehensive strength
approx. 3.5-7.5N/mm²

Thermal conductivity, λ_{10} , dry:
 $\leq 0.83 \text{ W/(mK)}$ for P = 50%
 $\leq 0.93 \text{ W/(mK)}$ for P = 90%

4. Application instructions

Substrate preparation

Test substrate for load carrying capacity. Remove loose parts and old coats mechanically or with a water pressure jet. Use Keim Universal Render as a first layer for rough textured existing render or uneven substrates.

Application

Mix in the ratio of 1 kg Keim Universal Render Fine to 0.27 - 0.29 litres of clean cold water (approximately 5.4 - 5.85 litres per 20kg bag) using a mechanical stirrer or plaster mixing machine/sprayer, e.g. Putzmeister or similar.

Do not over mix material, or re-mix material that has already set.

Apply to pre-wetted surfaces in layers from 4mm minimum to 8mm maximum. For subsequent application do not scratch up applied coat and leave for a minimum period of 12 hours before reapplication. Total thickness of render must be a minimum of 6mm.

Keim Glassfibre Reinforcing Mesh may be incorporated if required by pressing into newly applied Keim Universal Render Fine. When incorporating mesh, apply a first layer of Keim Universal Render Fine, flatten the fabric (with an overlap of 10cm) and apply the second layer of Keim Universal Render Fine.

Finish off using a float appropriate to the required surface finish (i.e. sponge faced float such as Keim Hydro Sponge Float).

Application conditions

Do not apply at ambient and base temperatures below 5°C. Keim Universal Render Fine should be protected from direct sun and rain during the setting time.



Setting Time

1 day per 1mm render layer thickness.

Subsequent Finishing

Keim Universal Render Fine is suitable for decoration with all exterior and interior Keim Mineral Paint systems after a minimum period of 15 days.

Consumption

Approximately 1.1kg/m² per 1mm render layer thickness.

The consumption rate is offered for guideline purposes only. Actual consumption rates should be determined by tests on trial areas.

Cleaning of tools

Clean immediately after use with water

5. Packaging

20kg packs

6. Storage

Approx. 12 months, if kept cool, but frost free in tightly closed containers.

7. Disposal

EC Waste Code No. 17 01 01

Any residues must be emptied out of sacks before recycling.

8. Safety instructions

Cover surfaces which are not to be painted, in particular glass, natural stone, ceramics etc. Protect the eyes and skin from splashes. Keep out of reach of children.

Refer to COSHH data sheet.

The stated values and properties are the result of extensive development work and practical experience. Our recommendations for application, whether given verbally or in writing, are intended to provide assistance in the selection of our products and do not establish a contractual relationship. In particular, they do not release those purchasing and applying our products from the duty of establishing for themselves, with due care, the suitability of our products for the intended application. Standard building industry practices must be complied with. We retain the right to make modifications to improve the products or their application. This edition supersedes all earlier editions.

**KEIM**

MINERAL PAINTS LTD

Santok Building
Deer Park Way, Donnington Wood
Telford, Shropshire, TF2 7NA
Tel. (01952) 231250
Fax (01952) 231251

www.keimpaints.co.uk
sales@keimpaints.co.uk