

Osmo Door Oil

Technical Data Sheet

The great eco-friendly finishing treatment from Osmo to protect and preserve all internal wooden doors and joinery.

- Osmo Door oil is easy to use and gives a professional touch to internal doors
- High quality and durable finish – microporous
- Natural oil/wax based
- Water repellent and indelible
- Does not crack, flake, peel or blister

Product Description: Osmo Door oil is a special oil and wax combination, used as a clear treatment on wooden doors and general internal joinery. Osmo door oil is made on a base of natural plant oils and waxes. The surface will be protected from common household substances such as wine, beer, fizzy drinks, coffee, tea, fruit juice, milk and water in accordance with DIN 68861-1A (German industrial norm).

Preparation: The wooden surface must be clean and dry (max. 20%moisture content). Clean or lightly sand old microporous stains. Remove old varnish (use Osmo Paint Remover or sand down). If necessary sand down the surface using fine sand paper (grit P120-150), remove dust carefully.

Application

Osmo Door-oil is a clear, simple to use treatment. Please do not thin. Shake well before use.

- Apply thinly, following the grain of the wood, with thick natural bristle paintbrush (Osmo Natural Bristle Brush for example), Osmo Micro-fibre Roller or with a lint free cloth.
- **Leave to dry overnight for at least 8-10 hours.**
- Allow for good ventilation
- Apply second coat as above
- Again leave this coat to dry for at least 8-10 hours with good ventilation
- If using a lint free cloth, apply 3-4 thin coats
- Cleaning your tools with either Osmo brush cleaner or turpentine.

Care and maintenance

Using Osmo Door-oil protects the door or any internal joinery from common household spillages, which can simply be cleaned off with water (or Osmo Wash and Care) and then wiped dry.

To remove stubborn stains, use Osmo liquid wax cleaner, that both cleans and regenerates the surface.

For occasional renovation, reapply Osmo door-oil thinly to a clean surface.

Ingredients

Based on natural vegetable oils (sunflower-oil, Thistle-oil, soyabean-oil) and waxes (carnauba wax and candelilla wax), Paraffins, lead free siccatives (drying agents) an water repellent additives; de-aromatized white spirit(benzene-free). This product fulfils EU-regulations (2004/42/EC) according to the VOC limit value of max. 400g/l (cat. A/E (2010)).

Coverage

Osmo Door-oil is also good value – A 1 litre tin will cover 12m² with 2 coats and has a shelf life of 5 years or more if can is tightly closed.