



OWATROL OIL



Paint Conditioner & Rust Inhibitor



Added Flow For Perfect Finishes

Owatrol Paint Conditioner is a unique paint additive that improves finish and eases application for the professional painter and decorator, especially in difficult conditions.

Owatrol added to any oil-based paint, varnishes or stains will beat paint drag – reducing brush marks and improving coverage.

Unlike thinners, which weaken the paint, Owatrol fortifies it – increasing penetration and adhesion to provide a longer-lasting finish that resists flaking and peeling.

Owatrol can be used to combat rust wherever it occurs, penetrating deeply to stabilise the rust and prevent it reforming. Because of Owatrol's 'wetting' properties, it penetrates through the rust to the sound metal, driving out any moisture and air; filling the rust pores with oil.

Owatrol bonds with the rust to form a flexible protective coating which may be painted over without further preparation

Do not overcoat or use Owatrol Oil with paints containing 'hot' solvents such as Xylene or two-part coatings.

**PROVIDES
EXCELLENT RUST
PROTECTION**

Improves Coverage

Ideal for Special Effects

Protects Against Rust

- **Coverage when use neat:**
Wood: 5-8m² per litre
Rusted Surfaces 8-12m² per litre
- **Drying Time:**
Neat on Wood – Overnight
Neat on Metal – 24 hours
As an Additive – Paint Manufacturers Guidelines
- **Sizes:**
500ml, 1ltr, 5ltr, 20ltr
- **Application:**
Brush, Roller, Spray



Makes painting difficult surfaces easy

Saves Time & Money

Eases Application

Eliminates Brush Marks