



# TEXTROL®

## PENETRATING OIL FINISH

### USAGE

- Exterior.
- Soft wood like red cedar, larch, pine, ash etc.
- Horizontal (decks, outdoor furniture...) and vertical (windows, doors, siding...) surfaces.
- For new wood, use SEASONITE® during the first year.

### PROPERTIES

- Penetrates deeply, isolates and protects from the inside.
- Impregnates.
- Does not create a film and therefore does not peel.
- Allows application wet-on-wet, saving time.
- Protects against humidity and its effects.
- Colourless – maintains the surface's natural aspect.
- Can be tinted or obtained in pre-tinted colours.
- Easy maintenance, local touch up.



Clear



Golden Oak



Rustic Oak

### APPLICATION

- Apply one coat of TEXTROL®.
- Let it penetrate 15-30 minutes.
- Repeat as many times as necessary until wood will not absorb any more (saturated).
- Apply wet-on-wet, do not allow drying between coats.
- Once surface is saturated, wipe off any excess product to avoid stains and traces of shine when dry.

Note: Oily look on surface will disappear over a few weeks after application.

COVERAGE RATE WHEN WORKING MULTI COAT <b>5 m<sup>2</sup>/l</b>	COVERAGE RATE FOR MAINTENANCE <b>10 to 12 m<sup>2</sup>/l</b>	APPLICATION TOOLS 	TEMPERATURE FOR APPLICATION +35°C +5°C 	DRYING TIME <b>24-48h</b>	CLEAN UP WHITE-SPIRIT 
---	--	--------------------------	---	------------------------------	------------------------------



EXTERIOR

### Owatrol International SL

C/Aragón 179, 5º - 08011 Barcelona - Spain  
Tel: +34 934 51 66 04 - Fax: +34 934 52 14 54  
info@owatrol.com - www.owatrol.com