

## PRODUCT DATA RUST-OLEUM® Waterproof 3486KIT.1/3486.5

### DESCRIPTION

Rust-Oleum® Waterproof is an instant leak repair coating based on solvent soluble high polymers (acrylic and alkyd binders) reinforced with fibres.

### MAIN PROPERTIES

A ready to use waterproofing repair compound for instant leak repairs in any weather condition - Ideal for repairs to roofs, gutters, drain pipes, ridge-pieces, sky lights, cornices, chimney stacks, pipes, etc. - Seals leaks instantly, even on damp or wet surfaces - Forms a durable elastic coating (1300%) that withstands temperature changes and UV-light - Bridges cracks up to 2 mm (larger cracks can be treated with a special reinforcement fleece) - Adheres to: roofing, felt, slate, corrugated, bitumen, asphalt, hard PVC, polyester, zinc, brickwork, aluminium, glass, tiles and many other substrates - Available in 5 litre packaging or in a handy 1 litre emergency repair set.

### RECOMMENDED USES

Waterproof finish of roofs, non-walkable terraces, gutters, ridge-pieces, chimney stacks, pipes, etc.

### TECHNICAL DATA

Appearance:	Fibre structure (gloss 60°: ± 45%)
Colour:	Dark grey
Density:	1,01 - 1,04 g/cm <sup>3</sup>
Solids Content:	In volume: 41 - 43%
	In weight: 49 - 53%
Recommended film thickness:	Wet film: 1000 micron (cons.: 1 l/m <sup>2</sup> )
	Dry film: 430 micron (cons.: 1 l/m <sup>2</sup> )
VOC-content:	Max. 500 g/l
Flashpoint:	40°C. Flammable

<b>Drying times</b>	20°C/50% r.h.
To touch:	4 hours
To recoat:	3 - 14 days with the same product. 6 weeks with a paint (see remarks).

### Coverage

Theoretical:	± 1 - 2,5 l/m <sup>2</sup>
Practical:	Practical coverage depends on many factors such as porosity and roughness of the substrate and material losses during application.

### SURFACE PREPARATION

Remove any standing water, algae, lichens and loose chippings thoroughly. Clean the spots to be repaired with a hard broom and wash with a wet sponge. After cleaning, 3486 can be applied directly on the substrate. Minimum wet film thickness 1 mm. In case of repeatedly repaired spots, important or active cracks, apply 3486 crosswise over the cracks or fissures.

### DIRECTION FOR USE

To ensure homogeneity the product should be thoroughly stirred prior to use

**Rust-Oleum Netherlands B.V.**  
Braak 1, 4704 RJ  
P.O. Box 138, 4700 AC  
Roosendaal, The Netherlands  
T +31 (0)165 593 636  
F +31 (0)165 593 600  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)  
[www.rust-oleum.eu](http://www.rust-oleum.eu)

**N.V. Martin Mathys S.A.**  
Kolenbergstraat 23  
3545 Zelem  
Halen, Belgium  
T +32 (0)13 460 200  
F +32 (0)13 460 201  
[info.be@ro-m.com](mailto:info.be@ro-m.com)  
[www.ro-m.com](http://www.ro-m.com)

**Rust-Oleum France S.A.S**  
11, Rue Jules Verne, B.P. 60039  
95322 St-Leu-la-Forêt Cedex  
France  
T +33 (0)1 30 40 00 44  
F +33 (0)1 30 40 99 80  
[info.fr@ro-m.com](mailto:info.fr@ro-m.com)  
[www.ro-m.com](http://www.ro-m.com)

**Rust-Oleum UK Ltd.**  
Rotterdam House  
116 Quayside  
Newcastle  
NE1 3DY  
United Kingdom  
T +44 (0)2476 717 329  
F +44 (0)2476 718 930  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)  
[www.rust-oleum.eu](http://www.rust-oleum.eu)

## PRODUCT DATA RUST-OLEUM® Waterproof 3486KIT.1/3486.5

### APPLICATION & THINNING

Brush:	Do not dilute.
Roller:	Do not dilute.
Air-atomised spray:	Not possible.
Airless spray:	Not recommended.
Spatula:	Do not dilute.
Thinning:	If preferred 3486 can be diluted with Rust-Oleum Thinner 7301.
Cleanup:	Direct with white spirit.

### APPLICATION CONDITIONS

Can be applied during all weather conditions, except for snow. (-10°C to +35°C).

### REMARKS

- Product can be recoated with Mathys Dakfill New, Coating PRT or Dac Alu.
- Never apply the product on polystyrene insulation or onto new concrete. Not suitable for use in swimming pools, ponds or baths.

### SAFETY

Consult Safety Data Sheet and Safety Information printed on the can.

### SHELLIFE / STORAGE CONDITIONS

5 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5° and 35°C.

**Rust-Oleum Netherlands B.V.**  
Braak 1, 4704 RJ  
P.O. Box 138, 4700 AC  
Roosendaal, The Netherlands  
T +31 (0)165 593 636  
F +31 (0)165 593 600  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)  
[www.rust-oleum.eu](http://www.rust-oleum.eu)

**N.V. Martin Mathys S.A.**  
Kolenbergstraat 23  
3545 Zelem  
Halen, Belgium  
T +32 (0)13 460 200  
F +32 (0)13 460 201  
[info.be@ro-m.com](mailto:info.be@ro-m.com)  
[www.ro-m.com](http://www.ro-m.com)

**Rust-Oleum France S.A.S**  
11, Rue Jules Verne, B.P. 60039  
95322 St-Leu-la-Forêt Cedex  
France  
T +33 (0)1 30 40 00 44  
F +33 (0)1 30 40 99 80  
[info.fr@ro-m.com](mailto:info.fr@ro-m.com)  
[www.ro-m.com](http://www.ro-m.com)

**Rust-Oleum UK Ltd.**  
Rotterdam House  
116 Quayside  
Newcastle  
NE1 3DY  
United Kingdom  
T +44 (0)2476 717 329  
F +44 (0)2476 718 930  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)  
[www.rust-oleum.eu](http://www.rust-oleum.eu)