

**PSX 1001**

MSDS UK 01 / EN Version 2

Print Date 9/19/2009

Revision date 28-06-09

**1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING****Product information**

**Trade name** : PSX 1001

**Recommended use** : coating

**Company** : PPG Coatings SPRL/BVBA  
Noordersingel 23  
B-2040 Borgerhout

**Telephone** : +32 3 3606470

**Telefax** : +32 3 3606435

**Emergency telephone number** : +31 20 4075210

**E-mail address** : **PMC.Safety@PPG.com**

**2. HAZARDS IDENTIFICATION****Symbol(s) :**

|| Highly flammable  
|| Harmful

**R-phrase(s) :**

|| HIGHLY FLAMMABLE.  
|| HARMFUL BY INHALATION, IN CONTACT WITH SKIN AND IF SWALLOWED.  
|| IRRITATING TO SKIN.  
|| HARMFUL TO AQUATIC ORGANISMS, MAY CAUSE LONG-TERM ADVERSE EFFECTS IN THE AQUATIC ENVIRONMENT.

**P-phrase(s) :**

|| Contains : reaction product, mixed diamid wax  
|| May produce an allergic reaction.

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

Components	EC No.	CAS-No.	DSD	Note	Classification	Concentration
xylene	215-535-7	1330-20-7	25th	Nota C	R10 Xn; R20/21 Xi; R38	>=2.50 - <10.00%
Solvent naphtha (petroleum), light arom.	265-199-0	64742-95-6		Nota H, Nota P	R10 N; R51/53 Xn; R65 Xi; R37 R66 R67	>=2.50 - <10.00%

## SAFETY DATA SHEET

This Safety Data Sheet is prepared in accordance with Annex II to Regulation (EC) No. 1907/2006.



PPG Protective &amp; Marine Coatings

**PSX 1001**

MSDS UK 01 / EN Version 2

Print Date 9/19/2009

Revision date 28-06-09

ethylbenzene	202-849-4	100-41-4	19th		F; R11 Xn; R20	>=1.00 - <2.50%
mesitylene	203-604-4	108-67-8	29th		R10 Xi; R37 N; R51, R53	>=1.00 - <2.50%
3-aminopropyltriethoxysilane	213-048-4	919-30-2	19th		Xn; R22 C; R34	>=1.00 - <2.50%
1,2,4-trimethylbenzene	202-436-9	95-63-6	24th		R10 Xn; R20 Xi; R36/37/38 N; R51, R53	>=2.50 - <10.00%
cumene	202-704-5	98-82-8	26th		R10 Xn; R65 Xi; R37 N; R51, R53	>=0.10 - <1.00%
dimethyl, methoxyphenyl siloxane with phenyl silsesquioxane methoxy-terminated		68957-04-0			Xn; R22	>=10.00 - <25.00%
reaction product, mixed diamid wax					R43 R53	>=0.10 - <1.00%
Stoddard solvent	232-489-3	8052-41-3			R10 N; R51/53 Xn; R65 R66, R67	>=0.10 - <1.00%
Dimethoxydimethylsilane	214-189-4	1112-39-6			F; R11 Xn; R22	>=2.50 - <10.00%

Producer declares that for R-phrases not mentioned in chapters 3, the entire amount of hazardous substances is below limits. For components with an occupational threshold limit value see chapter 8. The benzene content of this product is less than 0.1%. Nota P and H apply.

*If multiple components with identical identifiers appear, these have different hazardous properties, e.g. flashpoint.*

**4. FIRST AID MEASURES**

- General advice** : When symptoms persist or in all cases of doubt seek medical advice. Never give anything by mouth to an unconscious person.
- Eye contact** : Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart. Remove contact lenses. Seek medical advice.
- Skin contact** : Take off all contaminated clothing immediately. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
- Inhalation** : Remove to fresh air. Keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration. If unconscious place in recovery position and seek medical advice.
- Ingestion** : If accidentally swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.
- Burns** : If spills on clothing catch fire, wash with plenty of water. Remove loose clothing. Do not remove clothing that has melted to the skin. Obtain medical attention.

**PSX 1001**

MSDS UK 01 / EN Version 2

Print Date 9/19/2009

Revision date 28-06-09

**5. FIRE-FIGHTING MEASURES**

- Specific hazards during fire fighting** : As the product contains combustible organic components, fire will produce dense black smoke containing hazardous products of combustion (see section 10). Exposure to decomposition products may be a hazard to health. Cool closed containers exposed to fire with water spray. Do not allow run-off from fire fighting to enter drains or water courses.
- Special protective equipment for fire-fighters** : In the event of fire, wear self-contained breathing apparatus.
- Suitable extinguishing media** : Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide. Keep containers and surroundings cool with water spray.
- Extinguishing media which shall not be used for safety reasons** : Do NOT use water jet.

**6. ACCIDENTAL RELEASE MEASURES**

- Personal precautions** : Use personal protective equipment. Ventilate the area. Refer to protective measures listed in sections 7 and 8. Wear respiratory protection. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. Remove all sources of ignition.
- Environmental precautions** : Try to prevent the material from entering drains or water ways. If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods for cleaning up** : Clean with detergents. Avoid solvents. Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
- Additional advice** : Refer to section 15 for specific national regulation.

**7. HANDLING AND STORAGE****Handling**

- Safe handling advice** : Avoid exceeding of the given occupational exposure limits (see section 8). Use only in area provided with appropriate exhaust ventilation. Avoid contact with skin, eyes and clothing. Smoking, eating and drinking should be prohibited in the application area. Avoid inhalation of vapour or mist. For personal protection see section 8.
- Advice on protection against fire and explosion** : Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. When transferring from one container to another apply earthing measures and use conductive hose material. No sparking tools should be used. Operators should wear anti-static footwear and clothing and floors should be of the conducting type. Isolate from sources of heat, sparks and open flame. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). The product should only be used in areas from which all naked lights and other sources of ignition have been excluded. No smoking. The accumulation of contaminated rags and dry overspray, particularly in spray booth filters, may result in spontaneous combustion. Good housekeeping standards, regular safe removal of waste materials and regular maintenance of spray booth filters will minimise the risks of spontaneous combustion and other fire hazards.

**Storage**

**PSX 1001**

MSDS UK 01 / EN Version 2

Print Date 9/19/2009

Revision date 28-06-09

- Requirements for storage areas and containers** : Observe label precautions. Prevent unauthorized access. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store between 5 and 30°C (41 - 86 F) in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. Solvent vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Electrical installations / working materials must comply with the technological safety standards. Keep away from sources of ignition - No smoking. Store in accordance with the particular national regulations (see section 15).
- Further information** : A licence may be required for storage under the Petroleum Consolidation Act 1928. This product must be stored in accordance with the Highly Flammable Liquids and Liquefied Petroleum Gases Regulations 1972.
- Advice on common storage** : Keep away from oxidising agents and strongly acid or alkaline materials.

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION****Components on the national list and/or the European TLV list (98/24/EC):**

Components	CAS-No.	Value [mg/m <sup>3</sup> ]	Value [ppm]	Basis
xylene <i>can be absorbed through skin</i> <i>can be absorbed through skin</i>	1330-20-7	220	50	EH40 WEL TWA
		441	100	EH40 WEL STEL
		221	50	EU ELV TWA
		442	100	EU ELV STEL
Solvent naphtha (petroleum), light arom.	64742-95-6	125		ESIG TWA
ethylbenzene <i>can be absorbed through skin</i> <i>can be absorbed through skin</i>	100-41-4	441	100	EH40 WEL TWA
		552	125	EH40 WEL STEL
		442	100	EU ELV TWA
		884	200	EU ELV STEL
mesitylene	108-67-8	100	20	EU ELV TWA
		125	25	EH40 WEL TWA
1,2,4-trimethylbenzene	95-63-6	100	20	EU ELV TWA
		125	25	EH40 WEL TWA
cumene <i>can be absorbed through skin</i> <i>can be absorbed through skin</i>	98-82-8	125	25	EH40 WEL TWA
		250	50	EH40 WEL STEL
		100	20	EU ELV TWA
		250	50	EU ELV STEL

**Personal protective equipment****General advice**




- Respiratory protection** : When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits.

**PSX 1001**

MSDS UK 01 / EN Version 2

Print Date 9/19/2009

Revision date 28-06-09

- Hand protection** : For prolonged or repeated contact use protective gloves.  
Barrier creams may help to protect the exposed areas of skin, they should however not be applied once exposure has occurred.  
Skin should be washed after contact.  
Use chemical resistant gloves classified under Standard EN 374: Protective gloves against chemicals and micro-organisms.
- Recommended gloves: Viton  
Minimum breakthrough time: 480 min
- The recommended gloves are based on most common solvent in this product.
- When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended.  
NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.
- Eye protection** : Chemical resistant goggles must be worn.
- Skin and body protection** : Personnel should wear protective clothing. Skin should be washed after contact. Working clothes must not consist of textiles, which show a dangerous melting behaviour in case of fire. Workers should wear antistatic footwear.
- Additional advice**
- Environmental protection** : Refer to national regulations in chapter 15 for regulations on environmental protection.
- Personal protection**  
**Protective equipment** : Enclosing glasses, safety gloves and P2A2 half-face combi mask
- 



*Please contact your personal protection equipment supplier for further advice*

**9. PHYSICAL AND CHEMICAL PROPERTIES**

- Form** : viscous
- Colour** : various
- Odour** : aromatic mild
- Flash point** : 19.0 °C
- Note: Calculated
- Autoignition temperature** :
- Upper explosion limit** : 7.87 %(V)  
376.63 g/m3
- Lower explosion limit** : 0.94 %(V)  
45.68 g/m3

**SAFETY DATA SHEET**

This Safety Data Sheet is prepared in accordance with Annex II to Regulation (EC) No. 1907/2006.

**PPG Protective & Marine Coatings****PSX 1001**

MSDS UK 01 / EN Version 2

Print Date 9/19/2009

Revision date 28-06-09

<b>Density</b>	:	1.32 g/cm <sup>3</sup> at 20 °C
<b>Water solubility</b>	:	no data available
<b>pH</b>	:	
<b>Viscosity, dynamic</b>	:	4,600 mPa.s at 23 °C

**10. STABILITY AND REACTIVITY**

<b>Conditions to avoid</b>	:	Avoid temperatures above 60°C (140 F), direct sunlight and contact with sources of heat.
<b>Hazardous reactions</b>	:	Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.
<b>Hazardous decomposition products</b>	:	In case of fire hazardous decomposition products may be produced such as: Carbon dioxide (CO <sub>2</sub> ), carbon monoxide (CO), oxides of nitrogen (NO <sub>x</sub> ), dense black smoke.

**11. TOXICOLOGICAL INFORMATION**

<b>Product information</b>	:	There is no data available for this product. The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and classified for toxicological hazards accordingly. See Sections 3 and 15 for details.
<b>Acute oral toxicity</b>	:	May cause nausea, abdominal spasms and irritation of the mucous membranes.
<b>Acute inhalation toxicity</b>	:	Exposure to component solvent vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects. Such as: mucous membrane irritation, respiratory system irritation, adverse effects on kidney, liver and central nervous system. Symptoms and signs: headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases loss of consciousness.
<b>Skin irritation</b>	:	Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in desiccation of the skin. The product may be absorbed through the skin.
<b>Eye contact</b>	:	The liquid splashed in the eyes may cause irritation and reversible damage.
<b>Further information</b>	:	There is no data available for this product.

**Acute Toxicity Data for Components**

cumene(98-82-8)

<b>Acute oral toxicity</b>	:	LD50: 382 mg/kg (rat)
----------------------------	---	-----------------------

**12. ECOLOGICAL INFORMATION**

<b>Further information</b>	:	No data is available on the product itself. The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and is classified for ecotoxicological properties accordingly. See sections 3 and 15 for details. The product should not be allowed to enter drains, water courses or the soil.
----------------------------	---	--

**PSX 1001**

MSDS UK 01 / EN Version 2

Print Date 9/19/2009

Revision date 28-06-09

**13. DISPOSAL CONSIDERATIONS**

**Product** : The product should not be allowed to enter drains, water courses or the soil. Disposal together with normal waste is not allowed. Special disposal required according to local regulations.

**Waste key for the unused product** : The European Waste Catalogue classification of this product, when disposed of as waste is:

08 01 11 Waste paint and varnish containing organic solvents or other dangerous substances.

If this product is fully cured or mixed with other wastes, this code may no longer apply. If mixed with other wastes, the appropriate code should be assigned. For further information contact your local waste authority

**14. TRANSPORT INFORMATION**

Transport within user's premises: always transport in closed containers that are upright, labelled and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport to be in accordance with ADR for road, IMDG for sea and IATA for air transport:

UN-Number	:	1263
Proper shipping name	:	PAINT
Class	:	3
Packing group	:	II
Label	:	3
Proper shipping name (ADR)	:	PAINT

Marine Pollutant (IMDG)	:	-
EmS (IMDG)	:	F-E, S-E

Limited quantity (ADR)	:	Max. per inner pack. : 5.00 L
	:	Max. per outer pack. : 30.00 KG
Limited quantity (IMDG)	:	Max. per inner pack. : 5.00 L
	:	Max. per outer pack. : 30.00 KG

**15. REGULATORY INFORMATION**

The product is classified and labelled in accordance with Directive 1999/45/EC.

**Highly flammable****Harmful**

**PSX 1001**

MSDS UK 01 / EN Version 2

Print Date 9/19/2009

Revision date 28-06-09

	<b>R-phrase(s)</b>	:	R11	Highly flammable.
			R20/21/22	Harmful by inhalation, in contact with skin and if swallowed.
			R38	Irritating to skin.
			R52/53	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

	<b>S-phrase(s)</b>	:	S23	Do not breathe spray.
			S36/37	Wear suitable protective clothing and gloves.
			S38	In case of insufficient ventilation, wear suitable respiratory equipment.
			S61	Avoid release to the environment. Refer to special instructions/ Safety data sheets.

	<b>P-phrase(s)</b>	:	Contains : reaction product, mixed diamid wax
			May produce an allergic reaction.

The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation. The provisions of the national health and safety at work regulations apply to the use of this product at work.

**National legislation**

**Further information** : Petroleum (Consolidation) Act, 1928 and associated legislation., Highly Flammable Liquids and Liquefied Petroleum Gases Regulations, 1972., HS (G) 178, Spraying of Flammable Liquids, HSE., HS (G) 176, Storage of Flammable Liquids in Tanks, HSE., HS (G) 51, Storage of Flammable Liquid in Containers, HSE., HS (G) 37, An introduction to Local Exhaust Ventilation, HSE., Health and Safety at Work etc Act, 1974, and relevant Statutory Provisions., Environmental Protection Act, 1990 and associated legislation., The Special Waste Regulations, 1996 and amendments., The Chemicals (Hazard Information and Packaging for Supply) Regulations, 1994 and amendments., EH 40, Occupational Exposure Limits, HSE. Revised annually., HS(G) 53, Respiratory Protective Equipment - A Practical Guide for Users, HSE., HS(G) 97, A Step by Step guide to COSHH Regulations, HSE., EH 173, Monitoring Strategies for Toxic Substances, HSE.

**16. OTHER INFORMATION**

This product contains a complex mixture of hydrocarbons. Detailed information can be obtained from the producer.

**Explanation of R-phrases mentioned in section 3**

	xylene	R10	Flammable.
		R20/21	Harmful by inhalation and in contact with skin.
		R38	Irritating to skin.



## SAFETY DATA SHEET

This Safety Data Sheet is prepared in accordance with Annex II to Regulation (EC) No. 1907/2006.

PPG Protective &  
Marine Coatings**PSX 1001**

MSDS UK 01 / EN Version 2

Print Date 9/19/2009

Revision date 28-06-09

Solvent naphtha (petroleum), light arom.	R10	Flammable.
	R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
	R65	Harmful: may cause lung damage if swallowed.
	R37	Irritating to respiratory system.
	R66	Repeated exposure may cause skin dryness or cracking.
ethylbenzene	R67	Vapours may cause drowsiness and dizziness.
	R11	Highly flammable.
	R20	Harmful by inhalation.
	R10	Flammable.
mesitylene	R37	Irritating to respiratory system.
	R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
	R22	Harmful if swallowed.
3-aminopropyltriethoxysilane	R34	Causes burns.
	R10	Flammable.
1,2,4-trimethylbenzene	R20	Harmful by inhalation.
	R36/37/38	Irritating to eyes, respiratory system and skin.
	R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
	R10	Flammable.
cumene	R37	Irritating to respiratory system.
	R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
	R65	Harmful: may cause lung damage if swallowed.
	R22	Harmful if swallowed.
dimethyl, methoxyphenyl siloxane with phenyl silsesquioxane methoxy-terminated reaction product, mixed diamid wax	R43	May cause sensitization by skin contact.
	R53	May cause long-term adverse effects in the aquatic environment.
	R10	Flammable.
Stoddard solvent	R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
	R65	Harmful: may cause lung damage if swallowed.
	R66	Repeated exposure may cause skin dryness or cracking.
	R67	Vapours may cause drowsiness and dizziness.
	R11	Highly flammable.
Dimethoxydimethylsilane	R22	Harmful if swallowed.

This Safety Data Sheet is based on the Safety Data Sheets obtained from the producer/manufacturer or/and internet databases and valid regulations considering hazardous substances/preparations.

## Training advice:

Persons taking part in a turnover of hazardous products ought to be trained in product handling, safety and hygiene.

Drivers ought to be trained and obtain a certificate in accordance with the requirements of transport regulations (ADR).

Version: 2

Revision date 28.06.2009

The information contained in this safety data sheet is based on the present state of knowledge and current European and National legislation at the date of issue. The supplier reserves the right to modify data on the safety data sheet without further notice. Any change in data will normally be followed by the issue of a new safety data sheet. The user should

**SAFETY DATA SHEET**

*This Safety Data Sheet is prepared in accordance with Annex II to Regulation (EC) No. 1907/2006.*



**PPG Protective &  
Marine Coatings**

**PSX 1001**

MSDS UK 01 / EN Version 2

Print Date 9/19/2009

Revision date 28-06-09

check the date of issue and if more than 12 months have elapsed, then the data should only be used after checking with the nearest sales office of the supplier to establish that the data is still valid. As the specific conditions of use of the product are outside the suppliers control, the supplier is not responsible for the (negative) consequences of these specific conditions of use, which are outside of the suppliers control and which are not compliant with the handling, storage and other instructions in this safety data sheet.

After all component(s) stated on the relevant Technical Data Sheet have been mixed the safety precautions mentioned on each of the component(s) safety data sheets and labels should be used in assessing the safety precautions of the mixed product.