

SAFETY DATA SHEET

This Safety Data Sheet is prepared in accordance with Annex II to Regulation (EC) No. 1907/2006.

PPG Protective &
Marine Coatings**SIGMA AQUACOVER 35 (ND)**

MSDS UK 01 / EN Version 5

Print Date 9/19/2009

Revision date 28-06-09

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING**Product information**

Trade name : SIGMA AQUACOVER 35 (ND)
Technical data sheet number : For further information see Technical Data Sheet.

Recommended use : coating

Company : PPG Coatings SPRL/BVBA
 Noordersingel 23
 B-2040 Borgerhout

Telephone : +32 3 3606470

Telefax : +32 3 3606435

Emergency telephone number : +31 20 4075210

E-mail address : **PMC.Safety@PPG.com**

2. HAZARDS IDENTIFICATION**P-phrase(s) :**

|| Safety data sheet available for professional user on request.

Note

: Not a hazardous substance or preparation according to EC-directives 67/548/EEC or 1999/45/EC. Not a hazardous substance or preparation according to EC-directives 67/548/EEC or 1999/45/EC.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Components	EC No.	CAS-No.	DSD	Note	Classification	Concentration
butyldiglycol	203-961-6	112-34-5	25th		Xi; R36	>=1.00 - <2.50%
Naphtha (petroleum), hydrotreated light	265-151-9	64742-49-0		Nota H, Nota P	R10 Xn; R65 R66, R67	>=1.00 - <2.50%

|| *Producer declares that for R-phrases not mentioned in chapters 3, the entire amount of hazardous substances is below limits. For components with an occupational threshold limit value see chapter 8. The benzene content of this product is less than 0.1%. Nota P and H apply.*

If multiple components with identical identifiers appear, these have different hazardous properties, e.g. flashpoint.

4. FIRST AID MEASURES

General advice : When symptoms persist or in all cases of doubt seek medical advice. Never give anything by mouth to an unconscious person.

**SIGMA AQUACOVER 35 (ND)**

MSDS UK 01 / EN Version 5

Print Date 9/19/2009

Revision date 28-06-09

- Eye contact** : Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart. Remove contact lenses. Seek medical advice.
- Skin contact** : Take off all contaminated clothing immediately. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
- Inhalation** : Remove to fresh air. Keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration. If unconscious place in recovery position and seek medical advice.
- Ingestion** : If accidentally swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

5. FIRE-FIGHTING MEASURES

- Specific hazards during fire fighting** : Cool closed containers exposed to fire with water spray. Do not allow run-off from fire fighting to enter drains or water courses.
- Special protective equipment for fire-fighters** : Not applicable.
- Suitable extinguishing media** : Not combustible.
- Extinguishing media which shall not be used for safety reasons** : Not applicable.

6. ACCIDENTAL RELEASE MEASURES

- Personal precautions** : Use personal protective equipment. Ventilate the area. Refer to protective measures listed in sections 7 and 8. Material can create slippery conditions.
- Environmental precautions** : Try to prevent the material from entering drains or water ways. If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods for cleaning up** : Clean with detergents. Avoid solvents. Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
- Additional advice** : Refer to section 15 for specific national regulation.

7. HANDLING AND STORAGE

- Handling**
- Safe handling advice** : Avoid exceeding of the given occupational exposure limits (see section 8). Use only in area provided with appropriate exhaust ventilation. Avoid contact with skin, eyes and clothing. Smoking, eating and drinking should be prohibited in the application area. Avoid inhalation of vapour or mist. For personal protection see section 8.
- Storage**
- Requirements for storage areas and containers** : Observe label precautions. Prevent unauthorized access. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store between 5 and 30°C (41 - 86 F) in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. Keep from freezing! Store in accordance with the particular national regulations (see section 15).
- Advice on common storage** : Keep away from oxidising agents and strongly acid or alkaline materials.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components on the national list and/or the European TLV list (98/24/EC):

SIGMA AQUACOVER 35 (ND)

MSDS UK 01 / EN Version 5

Print Date 9/19/2009

Revision date 28-06-09

Components	CAS-No.	Value [mg/m ³]	Value [ppm]	Basis
butyldiglycol	112-34-5	67.5	10	EH40 WEL TWA
		101.2	15	EH40 WEL STEL
		67.5	10	EU ELV TWA
		101.2	15	EU ELV STEL

Personal protective equipment**General advice**

Respiratory protection : When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits.

Hand protection : For prolonged or repeated contact use protective gloves. Barrier creams may help to protect the exposed areas of skin, they should however not be applied once exposure has occurred. Skin should be washed after contact. Use chemical resistant gloves classified under Standard EN 374: Protective gloves against chemicals and micro-organisms.

Recommended gloves: Nitrile rubber

When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended.

NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

Eye protection : Chemical resistant goggles must be worn.

Skin and body protection : Personnel should wear protective clothing. Skin should be washed after contact. Working clothes must not consist of textiles, which show a dangerous melting behaviour in case of fire.

Additional advice

Environmental protection : Refer to national regulations in chapter 15 for regulations on environmental protection.

**Personal protection
Protective equipment** : Eye protection, safety gloves and combi mask P1A1



Please contact your personal protection equipment supplier for further advice

**SIGMA AQUACOVER 35 (ND)**

MSDS UK 01 / EN Version 5

Print Date 9/19/2009

Revision date 28-06-09

9. PHYSICAL AND CHEMICAL PROPERTIES

Form	:	viscous
Colour	:	various
Odour	:	characteristic
Flash point	:	
		Note: not applicable
Autoignition temperature	:	
Upper explosion limit	:	
		Note: not applicable
Lower explosion limit	:	
		Note: not applicable
Density	:	1.51 g/cm ³ at 20 °C
Water solubility	:	completely soluble
pH	:	
Viscosity, dynamic	:	1,900 mPa.s at 23 °C
Flow time	:	>= 60 s Transversal section: 6 mm Method: ISO 2431 (EN 535) 6 mm CUP

10. STABILITY AND REACTIVITY

Conditions to avoid	:	Avoid temperatures above 60°C (140 F), direct sunlight and contact with sources of heat.
Hazardous reactions	:	Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.
Hazardous decomposition products	:	After evaporation of water, combustion will generate: Carbon dioxide (CO ₂), carbon monoxide (CO), oxides of nitrogen (NO _x), dense black smoke.

11. TOXICOLOGICAL INFORMATION

Product information	:	There is no data available for this product. The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and classified for toxicological hazards accordingly. See Sections 3 and 15 for details.
Acute oral toxicity	:	May cause nausea, abdominal spasms and irritation of the mucous membranes.
Acute inhalation toxicity	:	Exposure to component solvent vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects. Such as: mucous membrane irritation, respiratory system irritation, adverse effects on kidney, liver and central nervous system. Symptoms and signs: headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases loss of consciousness.
Skin irritation	:	Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in desiccation of the skin. The product may be absorbed through the skin.
Eye contact	:	The liquid splashed in the eyes may cause irritation and reversible damage.
Further information	:	There is no data available for this product.

**SIGMA AQUACOVER 35 (ND)**

MSDS UK 01 / EN Version 5

Print Date 9/19/2009

Revision date 28-06-09

Acute Toxicity Data for Components**12. ECOLOGICAL INFORMATION**

Further information : No data is available on the product itself. The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and is not classified as dangerous for the environment. See section 3 for details on components. The product should not be allowed to enter drains, water courses or the soil.

13. DISPOSAL CONSIDERATIONS

Product : The product should not be allowed to enter drains, water courses or the soil. Disposal together with normal waste is not allowed. Special disposal required according to local regulations.

Waste key for the unused product : The European Waste Catalogue classification of this product, when disposed of as waste is:

08 01 12 Waste paint and varnish other than those mentioned in 08 01 11.

If this product is fully cured or mixed with other wastes, this code may no longer apply. If mixed with other wastes, the appropriate code should be assigned. For further information contact your local waste authority

14. TRANSPORT INFORMATION

Transport within user's premises: always transport in closed containers that are upright, labelled and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport to be in accordance with ADR for road, IMDG for sea and IATA for air transport:

Note

Not classified as dangerous in the meaning of transport regulations.

15. REGULATORY INFORMATION

Not a hazardous substance or preparation according to EC-directives 67/548/EEC or 1999/45/EC.

S-phrases(s) : S23 Do not breathe spray.
S38 In case of insufficient ventilation, wear suitable respiratory equipment.

**SIGMA AQUACOVER 35 (ND)**

MSDS UK 01 / EN Version 5

Print Date 9/19/2009

Revision date 28-06-09

P-phrase(s) : Safety data sheet available for professional user on request.

The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation. The provisions of the national health and safety at work regulations apply to the use of this product at work.

National legislation

Further information : HS (G) 37, An introduction to Local Exhaust Ventilation, HSE., Health and Safety at Work etc Act, 1974, and relevant Statutory Provisions., Environmental Protection Act, 1990 and associated legislation., The Special Waste Regulations, 1996 and amendments., The Chemicals (Hazard Information and Packaging for Supply) Regulations, 1994 and amendments., EH 40, Occupational Exposure Limits, HSE. Revised annually., HS(G) 53, Respiratory Protective Equipment - A Practical Guide for Users, HSE., HS(G) 97, A Step by Step guide to COSHH Regulations, HSE., EH 173, Monitoring Strategies for Toxic Substances, HSE.

16. OTHER INFORMATION

This product contains a complex mixture of hydrocarbons. Detailed information can be obtained from the producer.

Explanation of R-phrases mentioned in section 3

butyldiglycol	R36	Irritating to eyes.
Naphtha (petroleum), hydrotreated light	R10	Flammable.
	R65	Harmful: may cause lung damage if swallowed.
	R66	Repeated exposure may cause skin dryness or cracking.
	R67	Vapours may cause drowsiness and dizziness.

This Safety Data Sheet is based on the Safety Data Sheets obtained from the producer/manufacturer or/and internet databases and valid regulations considering hazardous substances/preparations.

Training advice:

Persons taking part in a turnover of hazardous products ought to be trained in product handling, safety and hygiene.

Version: 5

Revision date 28.06.2009

The information contained in this safety data sheet is based on the present state of knowledge and current European and National legislation at the date of issue. The supplier reserves the right to modify data on the safety data sheet without further notice. Any change in data will normally be followed by the issue of a new safety data sheet. The user should check the date of issue and if more than 12 months have elapsed, then the data should only be used after checking with the nearest sales office of the supplier to establish that the data is still valid. As the specific conditions of use of the product are outside the suppliers control, the supplier is not responsible for the (negative) consequences of these specific conditions of use, which are outside of the suppliers control and which are not compliant with the handling, storage and other instructions in this safety data sheet.

SAFETY DATA SHEET

This Safety Data Sheet is prepared in accordance with Annex II to Regulation (EC) No. 1907/2006.



**PPG Protective &
Marine Coatings**

SIGMA AQUACOVER 35 (ND)

MSDS UK 01 / EN Version 5

Print Date 9/19/2009

Revision date 28-06-09

After all component(s) stated on the relevant Technical Data Sheet have been mixed the safety precautions mentioned on each of the component(s) safety data sheets and labels should be used in assessing the safety precautions of the mixed product.

Technical data sheet number 7203